

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
V-173	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
Name of Operator Yates Petroleum Corporation		8. Farm or Lease Name Valentine "VI." State
Address of Operator 207 South 4th St., Artesia, NM 88210		9. Well No. 1
Location of Well UNIT LETTER <u>K</u> <u>2310</u> FEET FROM THE <u>South</u> LINE AND <u>1650</u> FEET FROM THE <u>West</u> LINE, SECTION <u>10</u> TOWNSHIP <u>15S</u> RANGE <u>33E</u> NMPM.		10. Field and Pool, or Wildcat Unders. Saunders Permo-Penn
11. Elevation (Show whether DF, RT, GR, etc.) 4188.4' GR		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 17-1/2" hole at 6:00 PM 10-18-82. Ran 11 joints of 13-3/8" 54# J-55 casing set at 455'. 1-Texas Pattern guide shoe set at 455'. Insert float set at 413'. Cemented w/450 sacks Class "C" with 2% CaCl<sub>2</sub>. Compressive strength of cement - 1250 psi in 12 hours. PD 6:30 AM 10-19-82. Bumped plug to 400 psi, released pressure and float held okay. Cement circulated 40 sacks to pit. WOC. Drilled out 9:00 PM 10-19-82. WOC 14 hours and 30 minutes. Cut off and welded on flow nipple. Reduced hole to 12-1/4". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Lu Anita D. O'Neil TITLE Engineering Secretary DATE 10-21-82

ORIGINAL SIGNED BY JERRY SEXTON TITLE  DATE OCT 26 1982  
CONDITIONS OF APPROVAL DISTRICT CLERK