

CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.E.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ For ☐
5. State Oil & Gas Lease No.
LG 883

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO TEST OR TO REFINISH OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT TO DRILL (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐ Name of Operator Yates Petroleum Corporation Address of Operator 207 South 4th St., Artesia, NM 88210 Location of Well UNIT LETTER <u>M</u> <u>990</u> FEET FROM THE <u>South</u> LINE AND <u>990</u> FEET FROM THE <u>West</u> LINE, SECTION <u>29</u> TOWNSHIP <u>16S</u> RANGE <u>32E</u> NE 1/4 15. Elevation (Show whether DF, RT, GR, etc.) 4242' GR 12. County Lea	7. Unit Agreement Name 8. Farm or Lease Name Bunker Hill WB State 9. Well No. 1 10. Field and Pool, or Wildcat Bunker Hill Grayburg
--	---

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER ☐	PLUG AND ABANDON ☐ CHANGE PLANS ☐	REMEDIAL WORK ☐ COMMENCE DRILLING OPS. ☐ CASING TEST AND CEMENT JOB ☒ OTHER ☐	ALTERING CASING ☐ PLUG AND ABANDONMENT ☐
---	--	---	---

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 26 joints of 8-5/8" 24# J-55 ST&C casing set at 1111'. 1-Texas Pattern notched guide shoe set at 1111'. Insert float at 1066'. Cemented w/250 sacks Pacemaker Lite, 3% CaCl₂ and 1/4# sack celloseal. Tailed in w/300 sacks Class "C" 2% CaCl₂. Compressive strength of cement-1250 psi in 12 hours. PD 10:00 PM 12-1-82. Bumped plug to 900 psi, released pressure and float held okay. Cement circulated 25 sacks. WOC. Drilled out 4:00 PM 12-2-82. WOC 18 hours. Nipped up and tested to 1000 psi for 30 minutes, okay. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry Sexton TITLE Production Supervisor DATE 12-13-82
 ORIGINAL SIGNED BY
 JERRY SEXTON
 DISTRICT 1 SUPR.
 APPROVED BY _____ TITLE _____ DATE JAN 6 1983
 CONDITIONS OF APPROVAL, IF ANY: