

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico			Northwestern New Mexico		
Rustler					
T. Anhy	1587	T. Canyon	T. Ojo Alamo	T. Penn. "B"	
T. Salt		T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"	
B. Salt	2692	T. Atoka	T. Pictured Cliffs	T. Penn. "D"	
T. Yates	2773	T. Miss	T. Cliff House	T. Leadville	
T. 7 Rivers		T. Devonian	T. Menefee	T. Madison	
T. Queen	3584	T. Silurian	T. Point Lookout	T. Elbert	
T. Grayburg		T. Montoya	T. Mancos	T. McCracken	
T. San Andres	4273	T. Simpson	T. Gallup	T. Ignacio Qtzite	
T. Glorieta		T. McKee	Base Greenhorn	T. Granite	
T. Paddock		T. Ellenburger	T. Dakota	T.	
T. Blinbry		T. Gr. Wash	T. Morrison	T.	
T. Tubb	7243	T. Granite	T. Todilto	T.	
T. Drinkard		T. Delaware Sand	T. Entrada	T.	
T. Abo	8000	T. Bone Springs	T. Wingate	T.	
T. Wolfcamp	Is 9528	T. XX Marker	9823	T. Chinle	
T. Penn.		T. Dolomite	10565	T. Permian	
T. Cisco (Bough C)		T.	T. Penn. "A"	T.	

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet	
No. 2, from.....to.....feet	
No. 3, from.....to.....feet	
No. 4, from.....to.....feet	

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	450	450	Surface, Redbeds	7870	9838	1868	Dolomite, Anhydrite, Sahle
450	1582	1132	Redbeds	9738	10430	682	Limestone, Chert, Dolomite
1582	2133	551	Redbeds, Anhydrite, Salt	10420	10865	445	Dolomite, Shale, Lime
2133	3100	967	Anhydrite, Salt				
3100	4230	1130	Anhydrite				
4230	4618	388	Anhydrite, Dolomite				
4618	5060	442	Dolomite				
5060	5160	100	Dolomite, Sand, Shale				
5160	5260	100	Dolomite, Chert, Limestone				
5260	5500	240	Dolomite, Anhydrite, Lime				
5500	5600	100	Dolomite, Anhydrite, Chert				
5600	5800	200	Dolomite				
5800	7060	1260	Dolomite, Shale, Lime, Sand				
7060	7280	220	Dolomite				
7280	7870	590	Dolomite, Sand, Shale				

RECEIVED
RECEIVED

JUL 1 1983
JUL 1 1983
O.C.D.
HOBBS OFFICE
JUL 1 1983