## STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

TOT AND WITH CHARGE		
we. er Cortes Acceives		
DISTRIBUTION	1	Ĺ <u> </u>
SANTA FE		
FILE		
U.S.O.S.	_	
LAND OFFICE		ļ
0.7.7.0.7		į.

Yates Petorleum Corporation

207 South 4th St., Artesia, NM 88210

WELL X

...... of Operator

1. Location of Well

## Ν

Form C-103

IOT PINS TIME CONTROL OF CONTROL	
We. or Cortes RECEIVES	OIL CONSERVATION DIVISIO
DISTRIBUTION	P. O. BOX 2088
SANTAFE	SANTA FE, NEW MEXICO 87501
FILE	

OTHER-

SUNDRY NOTICES AND REPORTS ON WELLS
100 NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DIEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
100 NOT USE TAPPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

East LINE, SECTION 23 TOWNSHIP 158 MANGE

	Kevised 19-1-78				
[	5a. Indicate Type of Lease				
	State X Fee				
	5, State Oll & Gas Lease No.				
	LG 880				
	7. Unit Agreement Name				
	8. Farm or Lease Name				
	Etcheverry WD State				
	9. Well No.				
	1				
	10. Field and Pool, or Wildcat				
nom'	aunders Permo Upper Penr				
HUM					
ι.					
	12. County				
	Lea				
Oth	er Data				
	TEROPE OF				

			<u></u>
	15. Elevation (Show whether 4166 GR	DF, RT, GR, etc.)	12. County Lea
	ck Appropriate Box To Indicate N F INTENTION TO:	Nature of Notice, Report or Oth	ner Data r REPORT OF:
PLAFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK  COMMENCE DRILLING OPNS.  CASING TEST AND CEMENT JQB  OTHER Intermediate C	ALTERING CASING  PLUG AND ABANDONMENT []  ASING [X
OTHER	od Operations (Clearly state all pertinent det	and aire pertinent dates including	estimated date of starting any proposed
Describe Proposed or Complete work) SEE RULE 1103.		dans, and give pertine in dates, inclinating	

660 FEET FROM THE North LINE AND 231.0 FEET F

Ran 105 joints of 8-5/8" 32% J-55 casing set 4230'. 1-Texas Pattern notched guide shoe set 4230°. Float collar set 4190°. Cemented w/1775 sacks Pacesetter Lite, 5#/sack salt and 1/4#/sack celloseal. Tailed in w/200 sacks Class "C" 1/4#/sack celloseal. Compressive strength of cement - 950 psi in 12 hours. PD 12:30 PM 5-23-83. Cement circulated 5 sacks. WOC. Drilled out 6:30 AM 5-24-83. WOC 18 hours. Nippled up and tested to 1000# for 30 minutes, okay. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

DISTRICT I SUPERVISOR	YITLE	DATE
ORIGINAL SIGNED BY JERRY SEXTON		MAY 27 1983
Canaday bodlet	Production Superviso	DE DAYE 5-25-83
ereby certify that the information above is true and comp	ete to the best of my knowledge and belief.	
·		

i k

MAY 26 1983 HOBBS OFFICE