Submit 3 Copies to Appropriate District Office

CONDITIONS OF AFFROVAL, IF ANY:

## State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103

Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240		OIL CONSERVA P.O. F		ON WELL API NO. 30-025-28070					
DISTRICT II P.O. Drawer DD, Artesia, NM 88210  Santa Fe, New Mexico 8			87504-2088	5. Indicate Type of L		FEE [			
DISTRICT III 1000 Rio Brazos Rd., Azzec, NM 87410					6. State Oil & Gas Lease No. VA-193				
SUNDRY NOTICES AND REPORTS ON WELLS  ( DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  (FORM C-101) FOR SUCH PROPOSALS.)					7. Lease Name or Unit Agreement Name				
1. Type of Well of Well WELL	GAS WELL	OTHER			State "Q"				
2. Name of Ope	charles B. Gil	lespie. Jr.			8. Well No.				
3. Address of O	perator	9. Pool name or Wildcat							
4. Well Location		Midland, Texas	/9/0.		Wildcat			$\dashv$	
		80 Feet From The Sou	th	Line and 6	60 Feet From T	he <u>West</u>	1	Line	
Section	4	Township 15S	Ra		NMPM Le	a	Count	y	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4208.6 GR 4224 KB									
Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data									
NOTICE OF INTENTION TO: SUB					SEQUENT RE	PORT OF:			
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK					Ai	LTERING CASING	3		
TEMPORARILY.	ABANDON	CHANGE PLANS		COMMENCE DRILLING	GOPNS. X P	LUG AND ABAND	ONMENT	r 🗌	
PULL OR ALTER	R CASING	CASING TEST AND CI	EMENT JOB						
OTHER: OTHER:					<del> </del>		<del></del>		
12. Describe Prowork) SEE R		tions (Clearly state all pertinent	desails, as	nd give pertinent dates, inclu	iding estimated date of st	tarting any proposed	d		
5/15/91:	5/15/91: Rigged up Grace Drilling Company Rig #467. Started drilling surface cement plug in 8 5/8" casing at 8:00 p.m. 5/15/91.								
5/16/91:	Drilled cement from 4138-4204'. Ran 7 $7/8$ " sidetrack bit, 2° bent sub and drilled with mud motor from 4204-4257'.								
5/22/91:	/22/91: Drilled 7 7/8" hole to 4965'. Ran 134 jts. 5 1/2" 15.5# J-55 casing set at 4940'. Cemented with 250 sx Halliburton class 'C' containing .4% HALAD 9. Plug down at 3:15 p.m. Ran temperature survey - top of cement outside 5 1/2" casing at 3720'. Rig released at 5:15 p.m. 5/22/91. Wait on completion unit.								
		e and copyriete to the best of my kno	mining Tri	l halief					
•	at the information above in tru	11 +	- TT		Manager	_ DATE6/0	3/91		
TYPE OR PRINT NA	David 11 11					TELEPHONE NO.9	<u>15-683</u>	<u>3-17</u> 6!	
(This space for Str						<b>L</b>	UN O	צו כ	
<b>.</b>		6 <b>25</b> 5		<b></b>		DATE			
APPROVED BY	DISTRIC		— п			- · <del>-</del>			