

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-79

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. LG 5986	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- P&A		7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation		8. Farm or Lease Name Falcon WI State
3. Address of Operator 105 South 4th St., Artesia, NM 88210		9. Well No. 1
4. Location of Well UNIT LETTER <u>L</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>4</u> TOWNSHIP <u>15S</u> RANGE <u>33E</u> NMPM.		10. Field and Pool, or Wildcat Penn Saunders Permo Upper
15. Elevation (Show whether DF, RT, GR, etc.) 4208.4' GR		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Notified NMOCD, Hobbs, NM in advance of plugging operations.
Set CIBP at 9750'. Muxed mud w/25# salt gel per/bbl of 10# brine.
Circulated hole w/mud. Cap CIBP w/10 sx cement.
Found freepoint approximately 4300' at Glorieta top. Notified Mr. J. T. Sexton,
NMOCD, Hobbs, and received verbal permission to set 25 sx plug inside casing at
top of Glorieta.
Spotted 25 sx plug at 5750'.
Shot casing at 4257' and pulled.
Spotted 75 sx cement plug 4303'. Tagged plug at 4140'.
Spotted 35 sx plug at 1498'.
Spotted 15 sx cement plug 30' to surface.
Cut off wellhead. Install dry hole marker.
Plugging completed 1-8-87.
Heavy mud between all plugs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Quanta Goodlett TITLE Production Supervisor DATE 1-13-87

APPROVED BY Lyle F. Turna TITLE OIL & GAS INSPECTOR DATE DEC 30 1988

CONDITIONS OF APPROVAL, IF ANY:

E

RECEIVED

RECEIVED
JAN 15 1987
OCD
MOBBS OFFICE