

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico			Northwestern New Mexico		
T. Rustler	1582	T. Canyon	T. Ojo Alamo	T. Penn. "B"	
T. Anhy		T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"	
T. Salt	2650	T. Atoka	T. Pictured Cliffs	T. Penn. "D"	
T. Salt	2728	T. Miss	T. Cliff House	T. Leadville	
T. Yates		T. Devonian	T. Menefee	T. Madison	
T. 7 Rivers	3534	T. Silurian	T. Point Lookout	T. Elbert	
T. Queen		T. Montoya	T. Mancos	T. McCracken	
T. Grayburg	4192	T. Simpson	T. Gallup	T. Ignacio Qtzite	
T. San Andres	5794	T. McKee	Base Greenhorn	T. Granite	
T. Glorieta		T. Ellenburger	T. Dakota	T.	
T. Paddock		T. Gr. Wash	T. Morrison	T.	
T. Blaine	7101	T. Granite	T. Todilto	T.	
T. Tubb		T. Delaware Sand	T. Entrada	T.	
T. Drinkard	7850	T. Bone Springs	T. Wingate	T.	
T. Abo	9275	T. XX Marker	T. Chinle	T.	
T. Wolfcamp Ls		T. Virgilian	T. Permian	T.	
T. Penn.		T.	T. Penn. "A"	T.	
T. Cisco (Bough C)		T.			

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
No. 2, from.....to.....feet.....
No. 3, from.....to.....feet.....
No. 4, from.....to.....feet.....

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	431	431	Surface, Redbeds				
431	1600	1169	Redbeds				
1600	1772	172	Redbeds, Anhydrite				
1772	3165	1393	Salt, Anhydrite				
3165	3343	178	Anhydrite				
3343	3764	421	Anhydrite, Salt				
3764	4188	424	Dolomite, Anhydrite				
4188	8321	4133	Dolomite				
8321	8764	443	Dolomite, Shale				
8764	8915	151	Shale				
8915	9053	138	Shale, Dolomite				
9053	9720	667	Shale, Dolomite, Lime				
9720	10245	525	Lime, Shale				