

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1981 O - 347-166

RECEIVED
APR 19 1983
CLC.D.
FEDERAL OFFICE

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
TOWNER PETROLEUM COMPANY
3. ADDRESS OF OPERATOR SUITE 300
16701 GREENSPPOINT PK DRIVE HOUSTON, TX 77060
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1,980' FNL AND 1,980' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE
NM-19857
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
NONE
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
FEDERAL 15
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
UNDES. SAUNDERS PERMO U. PENN
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SEC. 15- T-15S - R - 33E
12. COUNTY OR PARISH
LEA
13. STATE
NEW MEXICO
14. API NO.
N/A
15. ELEVATIONS (SHOW DF, KDB, AND WD)
4,180' 4,192'-KB

(NOTE: Report results of multiple completion or zone changes on Form 9-330.)

RECEIVED

APR 8 1983

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud Date: 01-15-83 to 51' W/16" Bit.
At 420' ran 10 jts. of 13 3/8", 48#, ST&C Casing. Cemented W/425 sx. class c and circ. Survey at 420'. Amhydrite and salt at 2,264'.
at 4,257' ran 110 jts. of 9 5/8" 36# & 40# csa. ST&C of K-55. Cement w/1,165 sx. of pacesetter lite c. Tailed w/200 sx. class c cement. full circulation. Survey at 5,424' was 2°, at 5,926' was 2 1/4°; at 6,261' was 2°, at 6,805' was 1 3/4°, dolomite and sand at 7,662'. Sand and lime at 9,642'. Survey 3/4° Spotted cmt. plug 10,500'-9,900' w/180sx class H neat. Run 238 jts. of 5 1/2" csa. Set at 9,842' KB. Tailed w/200sx. class H plus 5% cf-9 plus 4% TF-4 w/cello-o-seal.
Released rig 02-28-83, SI-WOCU. Perf. Wolfcamp at 9,752' well dead. recovered water and 1% oil. Testing.

Subsurface Safety Valve: Manu. and Type NONE Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED David R. Glass TITLE OPERATIONS MGR. DATE APRIL 5, 1983

ACCEPTED FOR RECORD

(Leave space for Federal or State office use)

APPROVED BY (ORIG. SGD.) DAVID R. GLASS
CONDITIONS OF APPROVAL APR 18 1983

DATE