Submit 3 Copies to Appropriate District Office

- State of New Mexico s and Natural Resources Department Energy, Min

Form C-103 Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

DISTRICT II P.O. Drawer DD, Artesia, NM 88210

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.		
30-025-28132	_/_	
5. Indicate Type of Lease STATE X FEE		
4 5 4 6 4 5 4 7 4 4 4 1		

DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410	6. State Oil & Gas Lease No. LG 5422	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BAD DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		
1. Type of Well: OIL GAS WELL OTHER P&A WELL	Robin UT State	
2. Name of Operator YATES PETROLEUM CORPORATION	8. Well No.	
3. Address of Operator 105 South 4th St., Artesia, NM 88210	9. Pool name or Wildcat Saunders Permo Upper Penn	
4. Well Location Unit Letter N : 660 Feet From The South Line as	nd 1980 Feet From The West Line	
Section 10 Township 15S Range 33E NMPM Lea County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4186.5 GR		
Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:		
PERFORM REMEDIAL WORK PLUG AND ABANDON X REMEDIAL		
TEMPOPARILY ABANDON	COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT	
ILL OR ALTER CASING CASING TEST AND CEMENT JOB		
OTHER: OTHER:		
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. Propose to plug and abandon well as follows: Pull rods and pump. Pull tubing anchor @ 9150' and 2-7/8" tubing. GBIH and retrieve @9832' Set CIBP on wireline @ 9840' and cap w/35' cement (Bough perfs 9865-9974'). Set CIBP on wireline @ 9180' and cap w/35' cement (Wolfcamp perfs 9216-9811). Spot 35 sx cement plug through tubing from 7860' (Abo top - 7804'). Perforate Glorieta top @ 5788', set cement retainer @ 5750' and squeeze w/50 sx. Perforate @ 4175'. Pump down 5½" casing and check for returns on 5½" x 8-5/8" annulus. Set retainer @ 4100'. If returns were good, circulate cement up 5½ x 8-5/8 annulus, if not squeeze perfs @ 4175' w/50 sx and leave 50' cement on top of retainer. Set 25 sx plug from 2650'(Base Salt @ 2592'). Set 25 sx plug from 500' (13-3/8" shoe @ 455') for \$\frac{1}{2} = \frac{1}{2} \text{Substitute Divis } \frac{1}{2} Substitute		
I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
SIONATURE LA COMMANDE TIME Produ		
TYPEOR PRINT NAME Juanita Goodlett	тецерноне но. 505/748-1471	
(This space for State Use) WHO INA! SIGNIO BY SURE! SEMION	MAR 3 1 1993	

APPROVED BY-

DETROIT I SUPPRIVISOR