

N. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. E-7564	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT TO DRILL (FORM C-101) FOR SUCH PROPOSALS.)

6. Indicate Type of Well OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
8. Name of Operator ELK OIL COMPANY		8. Farm or Lease Name East Kemnitz
9. Address of Operator P. O. BOX 310, ROSWELL, NEW MEXICO 88201		9. Well No. 2
10. Location of Well UNIT LETTER <u>G</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>27</u> TOWNSHIP <u>16S</u> RANGE <u>34E</u> N.M.P.M.		10. Field and Pool, or Wildcat S. Kemnitz Atoka Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 4086 Grd.		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
DRILL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

16. Description of Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud well on October 13, 1983. Drilled 17 1/4" hole to 390'. Ran 390' of 13 3/8" casing, cemented w/450 sx Class "C". Circulated cement; WOC 18 hours. Tested to 1000# for 30 minutes; test OK. Resume drilling a 11" hole to 4525'. Ran 4525' of 32# & 24# 8 5/8" casing, cemented w/2000 sx Halliburton light containing 15# salt, 5# gilsonite and 1/4# flocele/sx. Tailed w/200 sx Class "C" neat. Cement did not circulate. Ran temperature survey, top 900' from surface. WOC 18 hours, tested casing to 1000# for 30 minutes, test OK. Resume drilling.

17. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>[Signature]</u>	TITLE <u>President</u>	DATE <u>10/28/83</u>
ORIGINAL SIGNED BY JEFFY SEXTON DISTRICT 1 SUPERVISOR		
APPROVED BY <u>[Signature]</u>	TITLE <u></u>	DATE <u>OCT 31 1983</u>
CONDITIONS OF APPROVAL, IF ANY:		