

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
Rustler	1513	T. Canyon	T. Ojo Alamo
T. Anhy		T. Strawn	T. Kirtland-Fruitland
T. Salt	2572	T. Atoka	T. Pictured Cliffs
B. Salt	2652	T. Miss	T. Cliff House
T. Yates		T. Devonian	T. Menefee
T. 7 Rivers	3450	T. Silurian	T. Point Lookout
T. Queen		T. Montoya	T. Mancos
T. Grayburg	4110	T. Simpson	T. Gallup
T. San Andres	5712	T. McKee	Base Greenhorn
T. Glorieta		T. Ellenburger	T. Dakota
T. Paddock		T. Gr. Wash	T. Morrison
T. Blinebry	7023	T. Granite	T. Todilto
T. Drinkard	7773	T. Delaware Sand	T. Entrada
T. Abo	9174	T. Bone Springs	T. Wingate
T. Wolfcamp LS		T. XX Marker	9402
T. Penn.		T. Virgilian	9828
T. Cisco (Bough C)		T.	T. Permian
			T. Penn. "A"
			T. Penn. "B"
			T. Penn. "C"
			T. Penn. "D"
			T. Leadville
			T. Madison
			T. Elbert
			T. McCracken
			T. Ignacio Qtzite
			T. Granite

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....	feet.....
No. 2, from.....to.....	feet.....
No. 3, from.....to.....	feet.....
No. 4, from.....to.....	feet.....

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	500	500	Surface, Redbeds	4980	5400	420	Dolomite, Chert, Lime
500	1240	740	Shale	5400	5520	120	Dolomite
1240	1300	60	Shale, Anhydrite, Sand	5520	5740	220	Dolomite, Lime
1300	1600	300	Shale, Sand	5740	6388	648	Dolomite, Anhydrite
1600	1760	160	Shale, Anhydrite, Sand	6388	6970	582	Dolomite, Tr. Anhydrite
1760	1900	140	Shale, Sand	6970	7350	380	Anhydrite, Dolo, Sand, Sha
1900	2300	400	Shale, Anhydrite, Sand	7350	7800	450	Dolomite, Anydrite
2300	2340	40	Shale, Anhydrite, Lime	7800	9200	1400	Shale, Dolomite, Anhydrite
2340	2440	100	Shale	9200	9950	750	Dolomite, Lime, Shale
2440	2600	160	Shale, Salt	9950	10311	361	Lime, Shale
2600	3120	520	Shale, Anhydrite, Salt				
3120	3180	60	Shale, Anhy, Salt, Sand				
3180	4140	960	Shale, Anhydrite, Salt				
4140	4520	380	Shale, Anhydrite, Dolo.				
4520	4980	460	Dolomite, Anhydrite				

RECEIVED
APR 10 1984
O.C.D.
HOBBS OFFICE