

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
LG 959

SUNDRY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐
Name of Operator
Yates Petroleum Corporation
Address of Operator
207 South 4th St., Artesia, NM 88210
Location of Well
UNIT LETTER D 330 FEET FROM THE North LINE AND 990 FEET FROM
THE West LINE, SECTION 15 TOWNSHIP 15S RANGE 33E NMPM.

7. Unit Agreement Name
8. Farm or Lease Name
Coquina WK State
9. Well No.
2
10. Field and Pool, or Wildcat
Undes. Saunders Permo Upper Penn
12. County
Lea

15. Elevation (Show whether DF, RT, GR, etc.)
4192.3' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐
PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER Intermediate Casing ☒
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 99 joints of 8-5/8" 32# J-55 casing set 4195'. 1-Texas Pattern notched guide shoe set 4195'. Insert float set 4152'. Cemented w/1460 sacks Halliburton Lite, 1/4# flocele, 5#/ sack salt. Tailed in w/250 sacks Class "C" 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hours. PD 4:00 AM 11-26-83. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 50 sacks. WOC. Drilled out 10:00 PM 11-26-83. WOC 18 hours. Nipped up and tested to 1000 psi for 30 minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Jerry Sexton TITLE Production Supervisor DATE 11-29-83

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE DEC 1 1983

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

NOV 30 1983

NOBBY OFFICE