

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	2,090	T. Canyon		T. Ojo Alamo		T. Penn. "B"	
T. Salt		T. Strawn	11,545	T. Kirtland-Fruitland		T. Penn. "C"	
B. Salt		T. Atoka		T. Pictured Cliffs		T. Penn. "D"	
T. Yates		T. Miss		T. Cliff House		T. Leadville	
T. 7 Rivers	3,550	T. Devonian		T. Menefee		T. Madison	
T. Queen	4,220	T. Silurian		T. Point Lookout		T. Elbert	
T. Grayburg		T. Montoya		T. Mancos		T. McCracken	
T. San Andres	5,743	T. Simpson		T. Gallup		T. Ignacio Ottze	
T. Glorieta	6,628	T. McKee		Base Greenhorn		T. Granite	
T. Paddock	6,766	T. Ellenburger		T. Dakota		T.	
T. Blinebry		T. Gr. Wash		T. Morrison		T.	
T. Tubb	7,736	T. Delaware Sand		T. Todilto		T.	
T. Drinkard	7,926	T. Bone Springs	9,674	T. Entrada		T.	
T. Abo	8,540	T.		T. Wingate		T.	
T. Wolfcamp	10,173	T.		T. Chinle		T.	
T. Penn	10,917	T.		T. Permian		T.	
T. Cisco (Bough C)		T.		T. Penn "A"		T.	

OIL OR GAS SANDS OR ZONES

No. 1, from..... 10,660' to..... 10,680' No. 3, from..... to.....
No. 2, from..... to..... No. 4, from..... to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet

No. 2 from..... to..... feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary.)

From	To	Thickness in Feet	Lithology
9430	9500	70	Dolo, Sh
9500	9780	280	Dolo, Tr Lm
9780	10210	430	LS
10210	10370	160	LS, Sh
10370	10500	130	LS
10500	10630	130	LS, Sh
10630	10680	50	LS
10680	10770	90	LS, Sh, SS
10770	10850	80	LS
10850	11200	350	LS, Sh
11200	11300	100	Sh
11300	11380	80	LS, Sh
11380	11480	100	Sh, LS
11480	11550	70	LS, Sh, Dolo
11550	11610	60	LS, Sh, Dolo, Cht
11610	11690	80	LS
11690	11720	30	LS, Sh
11720	11840	110	LS

From	To	Thickness in Feet	Lithology
			

