

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

L CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation		8. Farm or Lease Name R.L. Anderson
3. Address of Operator P.O. Box 840 Seminole, Texas 79360		9. Well No. #1
4. Location of Well UNIT 11111 I 3437 FEET FROM THE North LINE AND 900 FEET FROM East 4 LINE, SECTION 16 S RANGE 37 E NMPM.		10. Field and Pool, or Wildcat UNDESIGNATED
15. Elevation (Show whether DF, RT, GR, etc.) GR 3820.1		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

PLUG & ABANDON (3-14-84)

Cement Plugs (Class "H" cmt) as follows:

Plug #1 75sx. 12160'-11910'	Plug #5 75sx. 6550'-6300'
Plug #2 75sx. 11655'-11405'	Plug #6 75sx. 5100'-4870'
Plug #3 75sx. 9780'-9530'	Plug #7 75sx. 2100'-1860'
Plug #4 75sx. 8500'-8250'	Plug #8 75sx. 500'-260'

Plug #9 10sx. Surface
Cut off 13 3/8" &
8 5/8" csg. at bottom
of cellar (5' deep)
and weld plate on top.

INTERMEDIATE CSG. (2-7-84)

8 5/8" 24# & 32# K-55 Csg. in 11" hole set @ 5015'. Cement with 1850sx. HLC + 15#/sk Salt + 1/4#/sk Flocele and 300sx Class "C" + 3#/sk Salt circulated 10sx. cmt to surface.

SURFACE CSG. (1-22-84)

13 3/8" 61# K-55 Csg. in 17 1/2" hole set @ 500'. Cement with 500sx Class "C" + 2% CaCl₂ - Circulated 50sx. cmt to surface.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED S. Butler TITLE Sr. Petroleum Engineer DATE April 2, 1984

APPROVED BY Ronald M. [Signature] TITLE OIL & GAS INSPECTOR DATE JAN 10 1985

CONDITIONS OF APPROVAL, IF ANY: