

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-77

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

10. Indicate Type of Lease	State ☒ Fee ☐
11. State Oil & Gas Lease No.	LG-1782

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - L-1 FORM C-101 FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER	7. Unit Agreement Name
2. Name of Operator Amoco Production Company	8. Farm or Lease Name State MC
3. Address of Operator P. O. Box 68, Hobbs, New Mexico 88240	9. Well No. 1
4. Location of well UNIT LETTER <u>J</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>11</u> TOWNSHIP <u>16-S</u> RANGE <u>33-E</u> N.M.P.M.	10. Field and Pool, or Wildcat Und. Queen
15. Elevation (Show whether DF, RT, GR, etc.) 4188.0' GL	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☒	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	OTHER <u>change plans</u> ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Reference verbal approval from Eddie Seay to P. B. McRae 6-28-84, granting permission for plug back and attempted completion in Queen formation. Drilled to a total depth of 13300'. Did not set production pipe. TIH with diverter tool on drill pipe to 12948' and spotted 130 sx class H cement with additives from 12948'-12748'. Pulled up and spotted plug from 12415'-12215' using 108 sx class H. Spotted plug from 10715'-10515' with 108 sx class H. Drilled out cement to 10500' and ran DST. RIH with drill pipe open ended and circulate spot 100 sx class H cement from 9660'-9460'. Spotted 120 sx class H cement from 8015'-7815'. Spotted 100 sx class H cement from 6040'-5840'. Spotted 162 sx class H cement with additives from 4600'-4200'. TIH and tagged cement at 4151' and drilled out to 4200' and displaced 8-5/8" casing with fresh water. Rig released 7-4-84.

0+5-NMOCD,H 1-J. R. Barnett, HOU Rm. 21.156 1-F. J. Nash, HOU Rm. 4.206 1-GCC

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Harry C. Clark</u>	TITLE <u>Assist. Admin. Analyst</u>	DATE <u>7-12-84</u>
APPROVED BY _____	TITLE _____	DATE <u>JUL 16 1984</u>
CONDITIONS OF APPROVAL, IF ANY:		

RECEIVED

JUL 13 1984

CLERK
HOBBS OFFICE