

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico				Northwestern New Mexico			
T. Rustler	2128	T. Canyon	10922	T. Ojo Alamo		T. Penn. "B"	
T. Anny	2216	T. Strawn	11320	T. Kirtland-Fruitland		T. Penn. "C"	
T. Salt	3139	T. Atoka		T. Pictured Cliffs		T. Penn. "D"	
T. Salt	3256	T. Miss		T. Cliff House		T. Leadville	
T. Yates		T. Devonian		T. Menefee		T. Madison	
T. 7 Rivers		T. Silurian		T. Point Lookout		T. Elbert	
T. Queen		T. Montoya		T. Mancos		T. McCracken	
T. Grayburg		T. Simpson		T. Gallup		T. Ignacio Qtzite	
T. San Andres	4942	T. McKee		T. Base Greenhorn		T. Granite	
T. Glorieta	6247	T. Ellenburger		T. Dakota		T.	
T. Paddock	6350	T. Gr. Wash		T. Morrison		T.	
T. Blinberry	7310	T. Granite		T. Todilto		T.	
T. Tubb	7989	T. Delaware Sand		T. Entrada		T.	
T. Drinkard	8322	T. Bone Springs		T. Wingate		T.	
T. Abo	9939	T. L. Strawn LS	11386	T. Chinle		T.	
T. Wolfcamp		T. Atoka Shale	11660	T. Permian		T.	
T. Penn.		T.		T. Penn. "A"		T.	
T. Cisco (Dough)	10476						

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....	feet.
No. 2, from.....to.....	feet.
No. 3, from.....to.....	feet.
No. 4, from.....to.....	feet.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	650	650	Surface, Redbeds	9950	10510	560	Dolomite, Chert, Lime
650	2582	1932	Redbeds, Anhydrite	10510	10870	360	Dolomite, Limestone
2582	4009	1427	Anhydrite, Salt Stringers	10870	11320	450	Shale, Dolomite, Lime
4009	4320	311	Anhydrite	11320	11850	530	Lime, Shale
4320	4550	230	Anhydrite, Shale, Sand, Dolo				
4550	5000	450	Anhydrite, Shale, Dolo.				
5000	5620	620	Dolomite				
5620	5750	130	Dolomite, Sand				
5750	5980	230	Dolomite				
5980	6200	220	Dolomite, Chert				
6200	6600	400	Dolomite, Limestone				
6600	6960	360	Dolomite				
6960	7300	340	Dolomite, Chert				
7300	7760	460	Dolomite				
7760	8120	360	Dolomite, Sand, Lime				
8120	9950	1830	Dolomite				

RECEIVED

JUL 12 1984

G.C.D.
HOBB'S OFFICE