

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☒ OTHER ☐

1. Name of Operator
Yates Petroleum Corporation

7. Unit Agreement Name

8. Farm or Lease Name

Shipp ZI

2. Address of Operator
207 South 4th St., Artesia, NM 88210

9. Well No.

1

3. Location of Well

UNIT LETTER C 660 FEET FROM THE North LINE AND 2310 FEET FROM

THE West LINE, SECTION 27 TOWNSHIP 16S RANGE 37E NMPM.

10. Field and Pool, or Wildcat
NE Lovington Penn

15. Elevation (Show whether DF, RT, GR, etc.)

3783.6' GR

12. County

Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

OTHER Intermediate Casing ☒

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 102 joints of 8-5/8" 32# J-55 ST&C casing set at 4325'. 1-Texas Pattern notched guide shoe set at 4325'. Float collar at 4280'. Cemented w/2100 sacks Halliburton Lite, 15#/sack salt and 1/4#/sack flocele. Tailed in w/250 sacks Class "H" 2% CaCl2. Compressive strength of cement - 875 psi in 12 hours. PD 10:00 PM 4-15-85. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 50 sacks to pit. WOC. Drilled out 10:00 AM 4-16-84. WOC 12 hours. Nippled up and tested to 1000 psi for 30 minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Production Supervisor

DATE 4-18-84

ORIGINAL SIGNED BY PORTY SEXTON
DISTRICT 1 SUPERVISOR

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

APR 24 1984