

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-73

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease

State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER C 660 FEET FROM THE North LINE AND 2310 FEET FROM

THE West LINE, SECTION 27 TOWNSHIP 16S RANGE 37E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name

Shipp ZI

9. Well No.

1

10. Field and Pool, or Wildcat

NE Lovington Penn

11. Elevation (Show whether DF, RT, GR, etc.)

3783.6' GR

12. County

Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPS. ☒

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

CHANGE PLANS ☐

CASING TEST AND CEMENT JOB ☒

OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole with rat hole machine at 10:00 AM 4-4-84. Set 40' of 20" conductor pipe. Began drilling a 17-1/2" hole with rotary tools at 7:15 AM 4-10-84. Ran 11 joints of 13-3/8" 54.5# J-55 casing set at 450'. 1-Texas Pattern notched guide shoe set at 450'. Insert float set at 408'. Cemented w/450 sacks Class "C" 2% CaCl₂. Compressive strength of cement - 1250 psi in 12 hours. PD 5:45 PM 4-10-84. Bumped plug to 300 psi, released pressure and float held okay. Cement circulated 50 sacks. WOC. Drilled out at 5:45 AM 4-11-84. WOC 12 hours. Cut off and welded on flow nipple. Reduced hole to 11". Drilled plug and resumed drilling. Note: Drilled plug, float and 50' of cement. Tagged cement at 400'.

6. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry Sexton

TITLE Production Supervisor

DATE 4-13-84

ORIGINAL SIGNED BY JERRY SEXTON

APPROVED BY DISTRICT 1 SUPERVISOR

TITLE _____

DATE APR 17 1984

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

16 1964

O.C.
HOBBS O.