TC5

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

DISTRICT II P.O. Drawer DD, Artesia, NM 88210 OIL CONSERVATIO 2040 Pacheco St. Santa Fe, NM 87	WELL API NO. 30-025-28695 sIndicate Type of Lease
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410	STATE FEE
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) TLease Name or Unit Agreement Name STATE NC	
Type of Well: OIL GAS WELL WELL OTHER SWD	
2Name of Operator TITAN RESOURCES I, INC. 4Well No. 1	
sAddress of Operator 500 WEST TEXAS, SUITE 500, MIDLAND, TEXAS 79701	
Well Location Unit Letter 1320 Feet From The NORTH	Line and 660 Feet From The EAST Line
	ange 32E NMPM LEA County
™Elevation (Show whether DF, RKB, RT, GR, etc. 4318' GR	
Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK PLUG AND ABANDON	REMEDIAL WORK ALTERING CASING
TEMPORARILY ABANDON CHANGE PLANS	COMMENCE DRILLING OPNS. PLUG AND ANBANDONMENT
PULL OR ALTER CASING CASING TEST AND CEMENT JOB	
	OTHER: ACIDIZE
taDescribe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 8/4/98 MIRU, PUMPED 5.5 BBLS 2% KCL WTR TO LOAD & PRESSURE 5 1/2 CSG; 8/5/98 REL PKR, MIRU TUBOSCOPE, SCAN TBG, FOUND HOLE IN TBG 201 JTS DOWN 8/6/98 TIH BIT & TBG, TAG @ 9508', REAMED & WASHED 9508-9984', DRILL 9984-9996', TAG BOTTOM 10,357'. 8/7/98 TIH TREATING PKR, SN & 30,4 JTS 2 7/8" TBG, TESTED TBG TO 7000 PSI ABOVE SLIPS, SET PKR 9445', TEST TO 560 PSI 8/8/98 ACIDIZED 5 1/2" PERFS FROM 9552-9558', 9910-9956' W/500 GALS 15% HCL ACID + AM540 SOLVENT, RU SWABBING EQUIP, MADE 25 RUNS, RD SWAB 8/9/98 TOH LD 304 JTS 2 7/8" TBG 8/11/98 TIH WIPKR, PROFILE NIPPLE, ON/OFF SKIRT & TBG, TESTED TBG TO 6000 PSI, PUMPED 190 BBLS FW MIXED W/55 GAL. SI-76 CORROSION INHIBITOR, SET PKR @ 9940' W/12,000# COMPRESSION 8/12/98 PRESSURE TESTED CSG TO 540 PSI & CHARTED 30 MIN CSG INTEGRITY TEST, NMOCD NOTIFIED BUT NO WITNESS PRESENT DURING TEST. RD WELL SERVICE	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
	ENGINEERING TECH DATE 08-17-98
TYPE OR PRINT NAME SHIRLEY MELTON	TELEPHONE NO. (915)498-8604
(This space for State Use) Orig. Signed by Paul Kautz	<i>^^~</i>
APPROVED BY Geologist TITLE	DATE DATE
CONDITIONS OF APPROVAL, IF ANY:	
ć 5	1300

