STATE (OF NEW ME	XICO	
JEGY AND M	INEPALS DE	PARTM	ENT
40. 07 (0*)			
DISTA	BUTION		
SANTAFE]
PILE			
U.S.O.S.			_
LAHO OFF	1C &		_
OPERATO			J
(DQ MOT	**************************************	4 FOR 1	RY NO
oir X	GAS WELL		от
. rame of Opera	tos		
	Charle	s B.	Gil
trees of Co.	eraior		

joints 17# J-55 and 47 joints 17# N 1 regular float shoe set 10130'. F Cemented with 780 sx type "H" 50/50 cement. Plug down 10:10 AM 7-3-84. released pressure and float held ok 7150' by temperature survey. 1 hereby certify that the information above is true and complete to the best of my knowledge and belief. TITLE	bumped prug to roou,
joints 17# J-55 and 4/ joints 1/# N 1 regular float shoe set 10130'. F Cemented with 780 sx type "H" 50/50 cement. Plug down 10:10 AM 7-3-84. released pressure and float held ok 7150' by temperature survey.	ay. WOC. Top cement
joints 17# J-55 and 4/ joints 1/# N l regular float shoe set 10130'. F Cemented with 780 sx type "H" 50/50 cement. Plug down 10:10 AM 7-3-84. released pressure and float held ok 7150' by temperature survey.	bumped prug to roou,
joints 17# J-55 and 4/ joints 1/# N 1 regular float shoe set 10130'. F Cemented with 780 sx type "H" 50/50 cement. Plug down 10:10 AM 7-3-84. released pressure and float held ok	bumped prug to roou,
joints 17# J-55 and 4/ joints 1/# N 1 regular float shoe set 10130'. F Cemented with 780 sx type "H" 50/50 cement. Plug down 10:10 AM 7-3-84. released pressure and float held ok	bumped prug to roou,
joints 17# J-55 and 4/ joints 1/# N 1 regular float shoe set 10130'. F Cemented with 780 sx type "H" 50/50 cement. Plug down 10:10 AM 7-3-84. released pressure and float held ok	bumped prug to roou,
joints 17# J-55 and 4/ joints 1/# N 1 regular float shoe set 10130'. F Cemented with 780 sx type "H" 50/50 cement. Plug down 10:10 AM 7-3-84. released pressure and float held ok	bumped prug to roou,
joints 17# J-55 and 4/ joints 1/# N 1 regular float shoe set 10130'. F Cemented with 780 sx type "H" 50/50 cement. Plug down 10:10 AM 7-3-84. released pressure and float held ok	bumped prug to roou,
joints 17# J-55 and 4/ joints 1/# N 1 regular float shoe set 10130'. F Cemented with 780 sx type "H" 50/50	poz .3% halad 22A Bumped plug to 1800#
joints 17# J-55 and 47 joints 17# N	TOAL COLLAR SEL TOUGH
$\frac{1}{1}$,	1/2" 17# N-80 154
1. (7-3-84) TD. 10130'. Ran 250 joints of 5 1/	2'' 17# N-80 and I-55
Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, work) SEE RULE 1103.	one comments and of states any proposed
OTHER	including estimated date of starting any proposes
L OR ALTER CASING CASING TEST AND CEMENT JOB	
PLUG AND ABANDON REMEDIAL WORK COMMENCE DRILLING OPMS.	PLUG AND ABANDONMENT
NOTICE OF INTENTION TO.	ALTERING CASING
Check Appropriate Box To Indicate Nature of Notice, Repor	t or Other Data
15. Elevation (Show whether DF, RT, GR, etc.) 4210 DF	Lea
THE East LINE, SECTION 3 TOWNSHIP 15-S MANCE 33-E	
UNIT LETTER I 1980 FEET FROM THE South LINE AND 660 F	
ocation of Well	10. Field and Paoi, or Wildcat
P.O. Box 8 Midland, TX 79702	9. Well No.
Charles B. Gillespie, Jr.	6. Form or Lease Name State "G"
OIL X GAS OTHER-	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR INCROSALS TO FAIL OF TO DIFFER ON PLUS DACA TO A DIFFERENT RESERVOIR. USE TAPPLICATION FOR PERMIT ATT FROM C-101) FOR SUCH PROPOSALS.)	7, Unit Agreement Nume
	E-2118-2
OPERATOR	State X Fos
LAND OFFICE OPERATOR	ta. Indicate Type of Leise
U.S.O.S. LAND OFFICE	
U.S.O.4. LAND OFFICE	Form C-101 Revised 10-1-1