

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-dilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico				Northwestern New Mexico			
Rustler	2036	T. Canyon	10956	T. Ojo Alamo	T. Penn. "B"		
T. Anhy		T. Strawn	11420	T. Kirtland-Fruitland	T. Penn. "C"		
T. Salt		T. Atoka	11730	T. Pictured Cliffs	T. Penn. "D"		
B. Salt		T. Miss	12697	T. Cliff House	T. Leadville		
T. Yates	3187	T. Devonian	13592	T. Menefee	T. Madison		
T. 7 Rivers		T. Silurian		T. Point Lookout	T. Elbert		
T. Queen	4066	T. Montoya		T. Mancos	T. McCracken		
T. Grayburg		T. Simpson		T. Gallup	T. Ignacio Qtzte		
T. San Andres	4862	T. McKee		Base Greenhorn	T. Granite		
T. Glorieta	6516	T. Ellenburger		T. Dakota			
T. Paddock		T. Gr. Wash		T. Morrison			
T. Blinbry		T. Granite		T. Todilto			
T. Tubb	Fullerton 7652	T. Delaware Sand		T. Entrada			
T. Drinkard		T. Bone Springs		T. Wingate			
T. Abo	8400	T. Virgilian	10576	T. Chinle			
T. Wolfcamp	LS 9720	T. Morrow LS	12234	T. Permian			
T. Penn.		T.		T. Penn. "A"			
T. Cisco (Bough C)							

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....	feet.
No. 2, from.....to.....	feet.
No. 3, from.....to.....	feet.
No. 4, from.....to.....	feet.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	85	85	Surface, Redbeds	13460	13670	210	Lime, Shale, Dolo, Sand
85	1609	1524	Redbeds	13670	13800	130	Dolomite, Lime, Shale
1609	2739	1130	Redbeds, Anhydrite				
2739	4020	1281	Anhydrite, Salt				
4020	5010	990	Shale, Anhydrite, Dolo.				
5010	5700	690	Dolomite, Anhydrite				
5700	6550	850	Dolomite				
6550	7100	550	Dolomite, Sand				
7100	8450	1350	Dolomite				
8450	9000	550	Dolomite, Shale, Anhy.				
9000	9380	380	Dolomite, Lime, Shale				
9380	9680	300	Dolomite, Shale, Anhy.				
9680	11460	1780	Lime, Dolo, Shale, Chert				
11460	12800	1340	Lime, Shale, Sand				
12800	13460	660	Lime, Shale				

RECEIVED

FEB - 4 1985

O.C.D.
NOTES OFFICE