

INSTRUCTIONS

This form is to be filled with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radioactivity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	T. Canyon	10526	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn		T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	11474	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss		T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian		T. Menefee	T. Madison
T. Queen	T. Silurian		T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya		T. Mancos	T. McCracken
T. San Andres	T. Simpson		T. Gallup	T. Ignacio Qtzite
T. Glorieta	T. McKee		Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger		T. Dakota	
T. Blinberry	T. Gr. Wash		T. Morrison	
T. Tubb	T. Granite	7072	T. Todilto	
T. Drinkard	T. Delaware Sand		T. Entrada	
T. Abo	T. Bone Springs	7828	T. Wingate	
T. Wolfcamp	T. XX Marker	9308	T. Chinle	
T. Penn.	T. Virgilian		T. Permian	
T. Cisco (Bough C)	T. Austin Cycle	12950	T. Penn. "A"	
	Mississippian	13365		

OIL OR GAS SANDS OR ZONES

No. 1, from	to	No. 4, from	to
No. 2, from	to	No. 5, from	to
No. 3, from	to	No. 6, from	to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from	to	feet
No. 2, from	to	feet
No. 3, from	to	feet
No. 4, from	to	feet

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	495	495	Surface, Redbeds	9420	9600	180	Lime
495	2400	1905	Redbeds, Salt	9600	9850	250	Lime, Shale, Chert
2400	2926	526	Anhydrite	9850	11880	2030	Lime, Shale
2926	3437	511	Lime	11880	12110	230	Lime, Shale, Sand
3437	3820	383	Anhydrite	12110	12430	320	Lime, Shale
3820	4269	449	Dolo, Anhydrite	12430	12520	90	Lime, Shale, Sand
4269	4600	331	Dolomite	12520	13370	850	Lime, Shale
4600	4850	250	Dolomite, Anhydrite	13370	13559	189	Shale, Lime, Sand
4850	5040	190	Anhy, Dolomite, Shale				
5040	5820	780	Dolomite				
5820	6600	780	Dolo, Anhydrite, Shale				
6600	7040	440	Dolomite				
7040	7120	80	Dolomite, Sand				
7120	7660	540	Dolomite				
7660	9310	1650	Anhy, Shale, Dolomite				
9310	9420	110	Limestone, Dolomite				