

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy <u>1280'</u>	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt <u>1390'</u>	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
T. Salt <u>2355'</u>	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates <u>2505'</u>	T. Miss <u>12355'</u>	T. Cliff House _____	T. Leadville _____
T. 7 Rivers <u>2795'</u>	T. Devonian <u>13515'</u>	T. Menefee _____	T. Madison _____
T. Queen <u>3380'</u>	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres <u>4180'</u>	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta <u>5655'</u>	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinbry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb sand <u>6850'</u>	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard <u>7055'</u>	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo <u>7580'</u>	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp <u>8885'</u>	T. _____	T. Chinle _____	T. _____
T. Penn. <u>CANYON</u>	T. _____	T. Permian _____	T. _____
T. Cisco <u>10645'</u>	T. _____	T. Penn. "A" _____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from _____ to _____	No. 4, from _____ to _____
No. 2, from _____ to _____	No. 5, from _____ to _____
No. 3, from _____ to _____	No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from <u>9715'</u> to <u>9799'</u> feet	_____
No. 2, from _____ to _____ feet	_____
No. 3, from _____ to _____ feet	_____
No. 4, from _____ to _____ feet	_____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
1280	1390	110'	Anhydrite	8885	10645	1760'	Wolfcamp-shale, sand, limestone
1390	2355	965'	Salt	10645	12355	1710'	Cisco Canyon-limestone, dol, shale, chert
2355	2505	150'	Anhydrite & shale				
2505	2795	290'	Yates } sand &				
2795	3380	585'	7 Rvrs } anhydrite	12355	13515	1160'	Mississippian-Limestone, shale
3380	4180	800'	Queen-Dolo				
4180	5655	1475'	San Andres-Dolo, Anhydrite, sand	13515	13700	185'	Devonian-Dolo
5655	6850	1195'	Glorietta-Dolo & sand				
6850	7055	205'	Tubb-Dolo, sand				
7055	7580	525'	Drinkard-Dolo, shale, sand				
7580	8885	1305'	Abo-Dolo, limestone, sand-shale, chert				

RECEIVED

AUG 27 1985

U.S. B.
FEDERAL OFFICE