

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run in the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico				Northwestern New Mexico			
Rustler	2177						
T. Anhy		T. Canyon	10900	T. Ojo Alamo		T. Penn. "B"	
T. Salt		T. Strawn	11226	T. Kirtland-Fruitland		T. Penn. "C"	
B. Salt		T. Atoka	11634	T. Pictured Cliffs		T. Penn. "D"	
T. Yates	3256	T. Miss		T. Cliff House		T. Leadville	
T. 7 Rivers		T. Devonian		T. Menefee		T. Madison	
T. Queen		T. Silurian		T. Point Lookout		T. Elbert	
T. Grayburg		T. Montoya		T. Mancos		T. McCracken	
T. San Andres	4968	T. Simpson		T. Gallup		T. Ignacio Qtzte	
T. Glorieta	6251	T. McKee		Base Greenhorn		T. Granite	
T. Paddock		T. Ellenburger		T. Dakota		T.	
T. Blinberry		T. Gr. Wash		T. Morrison		T.	
T. Tubb	7755	T. Granite		T. Todilto		T.	
T. Drinkard	7970	T. Delaware Sand		T. Entrada		T.	
T. Abo	8300	T. Bone Springs		T. Wingate		T.	
T. Wolfcamp Lm	10114	T. Lwr Strawn	11320	T. Chinle		T.	
T. Penn.		T.		T. Permian		T.	
T. Cisco (Bough C)	10466	T.		T. Penn. "A"		T.	

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....	feet.....
No. 2, from.....to.....	feet.....
No. 3, from.....to.....	feet.....
No. 4, from.....to.....	feet.....

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1860	1860	Surface, Redbeds				
1860	3924	2064	Redbeds, Anhydrite				
3924	4400	476	Anhydrite				
4400	4960	560	Anhydrite, Dolomite, Sand				
4960	7250	2290	Dolo, Tr. Chert & Shale				
7250	7830	580	Dolomite				
7830	8090	260	Dolo, Sand, Shale, Lime				
8090	8800	710	Dolomite				
8800	8970	170	Dolomite, Shale				
8970	9300	330	Dolomite				
9300	9410	110	Dolomite, Shale				
9410	9920	510	Dolomite				
9920	10880	960	Dolomite, Lime, Chert				
10880	11130	250	Lime, Shale, Chert				
11130	11862	732	Lime, Shale				