STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

DISTRIBUTION	
SANTA PE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

DISTRIBUTION	P. O. BOX 2088	Form C-103 ·
SANTA FE	SANTA FE, NEW MEXICO 87501	Revised 19-1-78
FILE]	5a. Indicate Type of Lease
U.S.O.S.		State Fee X
LAND OFFICE	·	
OPERATOR		5. State Oil & Gas Lease No.
SUNDR	RY NOTICES AND REPORTS ON WELLS	
(DO MOT USE THIS FORM FOR PRO USE "APPLICATI	DPOSALS TO DRILL OR TO OCCPEN OR PLUG BACK TO A DIPPERENT RESERVOIR. 100 FOR PERMIT —" (FORM C-101) FOR SUCH PROPOSALS.)	
		7, Unit Agreement Name
oil X SAS C	OTHER.	
Name of Operator		8. Form or Lease Name
Yates Petroleum (Corporation	Shipp "ZI"
Address of Operator		9. Well No.
	., Artesia, NM 88210	2
		10. Field and Pool, or Wildcat
ocation of Well		NT T
UNIT LETTER D 60	60 FEET FROM THE North LINE AND 1100 FEE	NE Lovington Penn
	•	
West Line section	ON 27 TOWNSHIP 16S RANGE 37E	_ HMPM. (()))))))))))))))))))))))))))))))))))
	15. Elevation (Show whether DF, RT, GR, etc.)	12. County
	3786.5' GR	Lea
Check A	Appropriate Box To Indicate Nature of Notice, Report	or Other Data
_ NOTICE OF IN	NTENTION TO: SUBSEC	QUENT REPORT OF:
RFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
MPORARILY ABANGON	COMMENCE DRILLING OPHS.	PLUE AND ABANDONMENT
)	CHANGE PLANS CASING TEST AND CEMENT JOS	7
)(CHANGE PLANS CASING TEST AND CEMENT JQS Pe	rforate & Treat
LL OR ALTER CASING		rforate & Treat X
)	Pe	rforate & Treat X
OTHER	OTHER PE	
OTHER	Pe	
OTHER	OTHER PE	
OTHER Describe Proposed or Completed Op work) SEE RULE 1503.	perations (Clearly state all pertinent details, and give pertinent dates, in	cluding estimated date of starting any proposed
OTHER Describe Proposed or Completed Op work) SEE RULE 1103. 1-9-85. Squeezed	perations (Clearly state all pertinent details, and give pertinent dates, in details) perforations 11526-532 thru cement retains	cluding estimated date of starting any proposed er that was set at 10505'.
Describe Proposed or Completed Opwork) SEE RULE 1703. 1-9-85. Squeezed Cemented w/150 sx	perations (Clearly state all pertinent details, and give pertinent dates, in d perforations 11526-532' thru cement retained Class H .5% Halad-9, .3% CFA and .1% HA-7.	eluding estimated date of starting any proposed er that was set at 10505'. Squeezed to 4000 psi.
Describe Proposed or Completed Opwork) SEE RULE 1603. 1-9-85. Squeezed Cemented w/150 sx WIH and perforate	d perforations 11526-532' thru cement retained Class H .5% Halad-9, .3% CFA and .1% HA-7. ed 11461-475' w/10 .42" holes as follows: 15	eluding estimated date of starting any proposed er that was set at 10505'. Squeezed to 4000 psi. 1461, 63, 65, 67, 69, 70,
Describe Proposed or Completed Opwork) SEE RULE 1703. 1-9-85. Squeezed Cemented w/150 sx WIH and perforate 71, 73 and 75'.	d perforations 11526-532' thru cement retained Class H .5% Halad-9, .3% CFA and .1% HA-7. ed 11461-475' w/10 .42" holes as follows: 1.50 Treated perforations 11461-475' w/500 gals	eluding estimated date of starting any proposed er that was set at 10505'. Squeezed to 4000 psi. 1461, 63, 65, 67, 69, 70,
Describe Proposed or Completed Opwork) SEE RULE 1703. 1-9-85. Squeezed Cemented w/150 sx WIH and perforate	d perforations 11526-532' thru cement retained Class H .5% Halad-9, .3% CFA and .1% HA-7. ed 11461-475' w/10 .42" holes as follows: 1.50 Treated perforations 11461-475' w/500 gals	eluding estimated date of starting any proposed er that was set at 10505'. Squeezed to 4000 psi. 1461, 63, 65, 67, 69, 70,
Describe Proposed or Completed Opwork) SEE RULE 1903. 1-9-85. Squeezed Cemented w/150 sx WIH and perforate 71, 73 and 75'.	d perforations 11526-532' thru cement retained Class H .5% Halad-9, .3% CFA and .1% HA-7. ed 11461-475' w/10 .42" holes as follows: 1.50 Treated perforations 11461-475' w/500 gals	eluding estimated date of starting any proposed er that was set at 10505'. Squeezed to 4000 psi. 1461, 63, 65, 67, 69, 70,
Describe Proposed or Completed Opwork) SEE RULE 1903. 1-9-85. Squeezed Cemented w/150 sx WIH and perforate 71, 73 and 75'.	d perforations 11526-532' thru cement retained Class H .5% Halad-9, .3% CFA and .1% HA-7. ed 11461-475' w/10 .42" holes as follows: 1.50 Treated perforations 11461-475' w/500 gals	eluding estimated date of starting any proposed er that was set at 10505'. Squeezed to 4000 psi. 1461, 63, 65, 67, 69, 70,
Describe Proposed or Completed Opwork) SEE RULE 1903. 1-9-85. Squeezed Cemented w/150 sx WIH and perforate 71, 73 and 75'.	d perforations 11526-532' thru cement retained Class H .5% Halad-9, .3% CFA and .1% HA-7. ed 11461-475' w/10 .42" holes as follows: 1.50 Treated perforations 11461-475' w/500 gals	eluding estimated date of starting any proposed er that was set at 10505'. Squeezed to 4000 psi. 1461, 63, 65, 67, 69, 70,
Describe Proposed or Completed Opwork) SEE RULE 1903. 1-9-85. Squeezed Cemented w/150 sx WIH and perforate 71, 73 and 75'.	d perforations 11526-532' thru cement retained Class H .5% Halad-9, .3% CFA and .1% HA-7. ed 11461-475' w/10 .42" holes as follows: 1.50 Treated perforations 11461-475' w/500 gals	eluding estimated date of starting any proposed er that was set at 10505'. Squeezed to 4000 psi. 1461, 63, 65, 67, 69, 70,
Describe Proposed or Completed Opwork) SEE RULE 1903. 1-9-85. Squeezed Cemented w/150 sx WIH and perforate 71, 73 and 75'.	d perforations 11526-532' thru cement retained Class H .5% Halad-9, .3% CFA and .1% HA-7. ed 11461-475' w/10 .42" holes as follows: 1.50 Treated perforations 11461-475' w/500 gals	eluding estimated date of starting any proposed er that was set at 10505'. Squeezed to 4000 psi. 1461, 63, 65, 67, 69, 70,
Describe Proposed or Completed Opwork) SEE RULE 1703. 1-9-85. Squeezed Cemented w/150 sx WIH and perforate 71, 73 and 75'.	d perforations 11526-532' thru cement retained Class H .5% Halad-9, .3% CFA and .1% HA-7. ed 11461-475' w/10 .42" holes as follows: 1.50 Treated perforations 11461-475' w/500 gals	eluding estimated date of starting any proposed er that was set at 10505'. Squeezed to 4000 psi. 1461, 63, 65, 67, 69, 70,
Describe Proposed or Completed Opwork) SEE RULE 1703. 1-9-85. Squeezed Cemented w/150 sx WIH and perforate 71, 73 and 75'.	d perforations 11526-532' thru cement retained Class H .5% Halad-9, .3% CFA and .1% HA-7. ed 11461-475' w/10 .42" holes as follows: 1.50 Treated perforations 11461-475' w/500 gals	eluding estimated date of starting any proposed er that was set at 10505'. Squeezed to 4000 psi. 1461, 63, 65, 67, 69, 70,
Describe Proposed or Completed Opwork) SEE RULE 1703. 1-9-85. Squeezed Cemented w/150 sx WIH and perforate 71, 73 and 75'.	d perforations 11526-532' thru cement retained Class H .5% Halad-9, .3% CFA and .1% HA-7. ed 11461-475' w/10 .42" holes as follows: 1.50 Treated perforations 11461-475' w/500 gals	eluding estimated date of starting any proposed er that was set at 10505'. Squeezed to 4000 psi. 1461, 63, 65, 67, 69, 70,
Describe Proposed or Completed Opwork) SEE RULE 1903. 1-9-85. Squeezed Cemented w/150 sx WIH and perforate 71, 73 and 75'.	d perforations 11526-532' thru cement retained Class H .5% Halad-9, .3% CFA and .1% HA-7. ed 11461-475' w/10 .42" holes as follows: 1.50 Treated perforations 11461-475' w/500 gals	eluding estimated date of starting any proposed er that was set at 10505'. Squeezed to 4000 psi. 1461, 63, 65, 67, 69, 70,
Describe Proposed or Completed Opwork) SEE RULE 1703. 1-9-85. Squeezed Cemented w/150 sx WIH and perforate 71, 73 and 75'.	d perforations 11526-532' thru cement retained Class H .5% Halad-9, .3% CFA and .1% HA-7. ed 11461-475' w/10 .42" holes as follows: 1.50 Treated perforations 11461-475' w/500 gals	eluding estimated date of starting any proposed er that was set at 10505'. Squeezed to 4000 psi. 1461, 63, 65, 67, 69, 70,
Describe Proposed or Completed Opwork) SEE RULE 1703. 1-9-85. Squeezed Cemented w/150 sx WIH and perforate 71, 73 and 75'.	d perforations 11526-532' thru cement retained Class H .5% Halad-9, .3% CFA and .1% HA-7. ed 11461-475' w/10 .42" holes as follows: 1.50 Treated perforations 11461-475' w/500 gals	eluding estimated date of starting any proposed er that was set at 10505'. Squeezed to 4000 psi. 1461, 63, 65, 67, 69, 70,
Describe Proposed or Completed Opwork) SEE RULE 1703. 1-9-85. Squeezed Cemented w/150 sx WIH and perforate 71, 73 and 75'.	d perforations 11526-532' thru cement retained Class H .5% Halad-9, .3% CFA and .1% HA-7. ed 11461-475' w/10 .42" holes as follows: 1.50 Treated perforations 11461-475' w/500 gals	eluding estimated date of starting any proposed er that was set at 10505'. Squeezed to 4000 psi. 1461, 63, 65, 67, 69, 70,
Describe Proposed or Completed Opwork) SEE RULE 1703. 1-9-85. Squeezed Cemented w/150 sx WIH and perforate 71, 73 and 75'.	d perforations 11526-532' thru cement retained Class H .5% Halad-9, .3% CFA and .1% HA-7. ed 11461-475' w/10 .42" holes as follows: 1.50 Treated perforations 11461-475' w/500 gals	eluding estimated date of starting any proposed er that was set at 10505'. Squeezed to 4000 psi. 1461, 63, 65, 67, 69, 70,
Describe Proposed or Completed Opwork) SEE RULE 1703. 1-9-85. Squeezed Cemented w/150 sx WIH and perforate 71, 73 and 75'.	d perforations 11526-532' thru cement retained Class H .5% Halad-9, .3% CFA and .1% HA-7. ed 11461-475' w/10 .42" holes as follows: 1.50 Treated perforations 11461-475' w/500 gals	er that was set at 10505'. Squeezed to 4000 psi. 1461, 63, 65, 67, 69, 70,

Production Supervisor

JAN 1 6 1985

ORIGINAL SIGNED BY JEES SEXTON DISTRICT | SUPERVISOR