

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. E-10160	

SUNDARY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name ---
2. Name of Operator Exxon Corporation		8. Farm or Lease Name New Mexico EJ State
3. Address of Operator P. O. Box 1600, Midland, TX 79702		9. Well No. 1
4. Location of Well UNIT LETTER <u>0</u> <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>2280</u> FEET FROM THE <u>East</u> LINE, SECTION <u>22</u> TOWNSHIP <u>16S</u> RANGE <u>34E</u> N14PM.		10. Field and Pool, or Wildcat Undesig. Kemnitz/Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 4073' GR		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

1-18-85 Spud 17-1/2"hole @ 1800.

1-19-85 Set 12 jts. 13-3/8"/54.5#/K55 csg. @ 501'. Cement w/ 550 sx ClC. Circ. Test csg. to 1800 psi for 30 min. Held OK. Woc approximately 48 hrs. before drillout.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Melba Kripling</u>	TITLE <u>Unit Head</u>	DATE <u>28 January 1985</u>
APPROVED BY <u>Eddie W. Seny</u>	TITLE <u></u>	DATE <u>JAN 31 1985</u>
CONDITIONS OF APPROVAL, IF ANY:		

RECEIVED

JAN 30 1985

O.C.
HOSBY OFFICE