

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico				Northwestern New Mexico			
Rustler	1550	T. Canyon		T. Ojo Alamo		T. Penn. "B"	
T. Anhy		T. Strawn	11871	T. Kirtland-Fruitland		T. Penn. "C"	
T. Salt		T. Atoka	12081	T. Pictured Cliffs		T. Penn. "D"	
B. Salt		T. Miss	13352	T. Cliff House		T. Leadville	
T. Yates	2792	T. Devonian		T. Menefee		T. Madison	
T. 7 Rivers		T. Silurian		T. Point Lookout		T. Elbert	
T. Queen	3980	T. Montoya		T. Mancos		T. McCracken	
T. Grayburg		T. Simpson		T. Gallup		T. Ignacio Qtzite	
T. San Andres	4500	T. McKee		Base Greenhorn		T. Granite	
T. Glorieta	5986	T. Ellenburger		T. Dakota		T.	
T. Paddock		T. Gr. Wash		T. Morrison		T.	
T. Blinbry		T. Granite		T. Todilto		T.	
T. Tubb	7160	T. Delaware Sand		T. Entrada		T.	
T. Drinkard		T. Bone Springs		T. Wingate		T.	
T. Abo	7880	T. Morrow	12620	T. Chinle		T.	
T. Wolfcamp	9522	T. Austin	12962	T. Permian		T.	
T. Penn.		T. Dunken	13352	T. Penn. "A"		T.	
T. Cisco (Bough C)							

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
No. 2, from.....to.....feet.....
No. 3, from.....to.....feet.....
No. 4, from.....to.....feet.....

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	550	550	Surface Shale, Redbeds	11020	11220	200	Shale, Lime, Dolomite
550	1180	630	Redbeds	11220	11480	260	Lime, Shale, Sand, Dolo.
1180	2961	1781	Redbeds, Anhydrite	11480	12000	520	Shale, Lime, Dolomite
2961	4550	1589	Anhydrite	12000	12640	640	Lime, Sh, Sd, Dolo, Cht
4550	4660	110	Dolomite, Shale	12640	13140	500	Lime, Sh, Sd, Cht
4660	5020	360	Dolomite	13140	13500	360	Shale, Lime
5020	5900	880	Dolomite, Cht, Anhydrite				
5900	6100	200	Dolomite, Lime, Sand				
6100	6700	600	Dolomite, Cht, Lime, Sand				
6700	7160	460	Dolomite, Cht, Anhydrite				
7160	7390	230	Dolomite, Sand				
7390	7880	490	Dolomite, Anhydrite				
7880	9450	1570	Dolomite, Anhydrite, Shale				
9450	11020	1570	Lime, Dolo, Cht, Shale				

RECEIVED

AUG -7 1985

100-100000-100000