

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-73

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
LG 4223	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input type="checkbox"/> GAS <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name	
2. Name of Operator		8. Farm or Lease Name	
Yates Petroleum Corporation		Hot Toddy ABQ State	
3. Address of Operator		9. Well No.	
207 South 4th St., Artesia, NM 88210		1	
4. Location of Well		10. Field and Pool, or Wildcat	
UNIT LETTER <u>G</u> , 1980 FEET FROM THE <u>North</u> LINE AND 1500 FEET FROM		Undes.	
THE <u>East</u> LINE, SECTION <u>18</u> TOWNSHIP <u>16S</u> RANGE <u>34E</u> NMPM.		S. Remnitz Atoka Morrow	
15. Elevation (Show whether DF, RT, GR, etc.)		12. County	
4141.1' GR		Lea	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
FULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐  
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☒  
CASING TEST AND CEMENT JOBS ☒  
OTHER ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐  
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 17-1/2" hole 2:30 PM 2-6-85. Ran 13 joints 13-3/8" 54.5# J-55 casing set at 550'. 1-guide shoe set at 550'. Insert float set at 507'. Cemented w/675 sx Class C 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hrs. PD 3:45 AM 2-7-85. Bumped plug to 750 psi, released pressure, held okay. Cement circulated 50 sx to pit. WOC. Drilled out at 3:45 PM 2-7-85. WOC 12 hrs. Cut off and welded on flow nipple. Reduced hole to 11". Drilled plug and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry Sexton

TITLE Production Supervisor

DATE 2-11-85

ORIGINAL SIGNED BY JERRY SEXTON

APPROVED BY DISTRICT I SUPERVISOR

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

FEB 14 1985

RECEIVED

FEB 13 1985

O.S.S.  
HOME OFFICE