

Submit 3 Copies To Appropriate

District Office

DISTRICT I

1625 N. French Dr., Hobbs, NM 88240

DISTRICT II

811 South First, Artesia NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

2040 S. Pacheco, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

2040 South Pacheco

Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.

30-025-29132

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

A-1320

7. Lease Name or Unit Agreement Name:

New Mexico -EQ- State

8. Well No.

1

9. Pool name or Wildcat

Shoebar, Strawn Northwest

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

TMBR/Sharp Drilling, Inc.

3. Address of Operator

P. O. Drawer 10970, Midland, TX 79702

4. Well Location

Unit letter J : 1980 feet from the South line and 1980 feet from the East line

Section

16

Township

16S

Range

35E

NMPM

County Lea

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

4003' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. Set CIBP @ 11,700' KB. Cap CIBP w/35' cement.

2. Displace well with 10 ppg gelled brine water.

3. Cut 5 1/2" casing @ 9950' KB. Pull and lay down casing. Set stub cement plug from 9900 to 10,000' KB. WOC. Tag plug.

4. Spot 100' cement plug from 8296' to 7296' KB.

5. Spot 100' cement plug from 7536' to 6536' KB.

6. Spot 100' cement plug across 9 5/8" casing shoe from 5050' to 4950' KB. WOC. Tag plug.

7. Spot 100' cement plug from 2185' to 2085' KB.

8. Spot 100' cement plug from 568' to 468' KB. — TAG

9. Spot 10 sx surface plug

10. Install dry hole marker.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

*Jeffrey D. Phillips*

TITLE

Vice President

DATE

3/31/2000

Type or print name

Jeffrey D. Phillips

Telephone No. (915) 699-5050

(This space for State use)

APPROVED BY

TITLE

DATE

Conditions of approval, if any:

