

INSTRUCTIONS

This form is to be filled with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filled in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico				Northwestern New Mexico			
Cisco							
T. Anhy	2153	T. Canyon	Shale 10920	T. Ojo Alamo		T. Penn. "B"	
T. Salt		T. Strawn	11294	T. Kirtland-Fruitland		T. Penn. "C"	
D. Salt		T. Atoka	11658	T. Pictured Cliffs		T. Penn. "D"	
T. Yates	3240	T. Miss		T. Cliff House		T. Leadville	
T. 7 Rivers		T. Devonian		T. Menefee		T. Madison	
T. Queen		T. Silurian		T. Point Lookout		T. Elbert	
T. Grayburg		T. Montoya		T. Mancos		T. McCracken	
T. San Andres	4984	T. Simpson		T. Gallup		T. Ignacio Qtzite	
T. Glorieta	6288	T. McKee		Base Greenhorn		T. Granite	
T. Paddock	6362	T. Ellenburger		T. Dakota		T.	
T. Blinbry		T. Gr. Wash		T. Morrison		T.	
T. Tubb	7788	T. Granite		T. Todilto		T.	
T. Drinkard	7960	T. Delaware Sand		T. Entrada		T.	
T. Abo	8280	T. Bone Springs		T. Wingate		T.	
T. Wolfcamp LS	10132	T. Lwr Strawn	11444	T. Chinle		T.	
T. Penn.		T.		T. Permian		T.	
T. Cisco (Bough C)	10502	T.		T. Penn. "A"		T.	

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....	feet.....
No. 2, from.....to.....	feet.....
No. 3, from.....to.....	feet.....
No. 4, from.....to.....	feet.....

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	350	350	Surface, Redbeds	6800	7100	300	Dolomite, Anhydrite, Sand
350	455	105	Redbeds, Anhydrite	7100	7660	560	Dolo, Cht, Anhy, Sand
455	2019	1564	Redbeds	7660	7900	240	Dolomite, Anhydrite
2019	2198	179	Anhydrite	7900	8020	120	Dolomite, Cht, Sand
2198	3816	1618	Anhydrite, Salt	8020	8840	820	Dolomite
3816	4300	484	Anhydrite, Lime	8840	8960	120	Dolomite, Shale
4300	4560	260	Anhy, Shale, Sand, Lime	8960	9280	320	Dolomite
4560	4720	160	Shale, Anhy, Dolo.	9280	9680	400	Dolomite, Shale
4720	4960	240	Anhydrite, Dolomite	9680	9880	200	Dolo, Anhy, Lime, Shald
4960	5060	100	Anhy, Dolo, Sand, Shale	9880	10600	720	Dolo, Lime, Cht, Shale
5060	5260	200	Dolomite, Sand	10600	11620	1020	Lime, Shale, Chert
5260	5540	280	Dolomite	11620	11850	230	Lime, Shale, Cht, Sd, Dolo.
5540	6300	760	Dolo, Anhydrite, Chert				
6300	6600	300	Dolomite, Anhydrite, Sand				
6600	6800	200	Dolomite, Anhydrite				