STATE OF NEW MEXICO IRGY AND MINERALS DEPARTMENT

we, ar torics hillings	OIL CONSERVATION DIVISI	
DISTRIBUTION	P. O. BOX 2088	Forn 0-103 Revised 10-1-33
SANTA PE	SANTA FE, NEW MEXICO 87501	
FILE		Sa. Indicate Type of Leave
V.S.G.4.		State X Fra
LAND OFFICE		S. State Ot. S. Gras Gease No.
OPERATOR		E-2116-2
		10-2110-2
SUNDRY	NOTICES AND REPORTS ON YELLS	
(DD NOT USE THIS FORM FOR SENTRON	NUTICES AND ICCITUTES ON TELLS SALS TO OFFICE OF TO THE PERSON OF PERSONS A DIFFERENT HE FOR PERMIT IN FORM CHICK FOR SUCH PROPOSALS.)	5 CH V 2 M
		7, Unit Agreement Nome
mett X	OTHER-	
ime of Operator		8. Farm or Lease Name
Charles B. Gillespi	io Tr	State "F"
Great of Operator	le, ui.	9. Well No.
•		6
P.O. Box 8, Midl	land, TX /9/02	10. Field and Posi, or Wildcat Penr
cation of Well		
E 21	20 FEET FROM THE North LINE AND 400	Saunders Permo Upper
West	2 TOWNSHIP 15-S MANGE 33-	E AMEN (IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII
THE CINE, SECTION		
	15. Elevation (Show whether DF, RT, GR, etc.)	12. County
	4184.5 GR	Lea
Check Ap	propriate Box To Indicate Nature of Notice,	•
NOTICE OF INT	ENTION TO:	SUBSEQUENT REPORT OF:
		A
FORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
PORARILY ASAHOON	COMMENCE DRILLING	OPHS. PLUG AND ABANDONMENT
OR ALTER CASING	CHANGE PLANS CASING TEST AND CEN	MENT IQE X
	OTHER	
)THER		

- 1. Ran 247 Joints of 5 1/2" 17# N-80 & K-55 LT & C casing set at 10122'.
- Cemented with 1025 sx Halliburton 50/50 POZ Class "H" cement. Pumped 2. plug and started displacement. Cement bridged off with 62 bbls left to displace with 5000 psi on casing at 6:01 pm. 8/28/85. Top of cement inside 5 1/2" casing at 7421'.
- 3. Will drill out cement, and run Cement Bond Log to determine top of cement outside 5 1/2" casing.

thy certify that the information above is true and compl	lete to the be	est of my knowledge and belief.	
2' 2 /			
Murd Harto	TITLE	Engineer	B/29/85
ORIGINAL SIGNED BY JERRY SEXTON	717LE	Engineer	SEP - 4 1985