

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation	8. Farm or Lease Name Andrus 9
3. Address of Operator Box D, Monument, New Mexico 88265	9. Well No. 1
4. Location of Well UNIT LETTER <u>L</u> <u>1874</u> FEET FROM THE <u>South</u> LINE AND <u>766</u> FEET FROM THE <u>West</u> LINE, SECTION <u>9</u> TOWNSHIP <u>16S</u> RANGE <u>37E</u> N.M.P.M.	10. Field and Pool, or Wildcat N.E. Lovington Penn.
15. Elevation (Show whether DF, RT, GR, etc.) 3842' KB, 3841' DF, 3823' GR	12. County Lea

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11-15-85 - Ran 41 jts. 5-1/2" 20# L-80 SS Buttress thd. csg., 239 jts. 5-1/2" 17# L-80 FRW csg. & 7 jts. 5-1/2" 17# L-80 SS csg. Set total of 239 jts. 5-1/2" csg. at 12,000'. Western Co. cemented 5-1/2" csg. w/500 sks. Class H cement plus 1.25% Flo-lok I plus 2/10% WR-2. Slurry wt. 15.6# per gal. Yield 1.18 cu.ft.per sk. Plug down 11:11 PM 11-15-85. Closed in 96 hrs. Ran bit & csg. scraper & checked float collar at 11,916'. Ran logs. Found top of cement outside 5-1/2" csg. at 10,100'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E. W. Seay TITLE Supv. Adm. Ser. DATE 1-8-86

APPROVED BY Eddie W. Seay TITLE Oil & Gas Inspector DATE JAN 10 1986

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JAN 10 1986

O.C.D.
HOBBS OFFICE