

EXXON COMPANY, U.S.A.
F.B. STATE NO.1

PAGE 4
02:08:15

1-V9CS FROM WT-V4S:D701

00/00/00

MEASURED	INCL.	HOLE	COURSE	TRUE	VERTICAL	VERTICAL	SECTION	RECTANGULAR	CLOSURE	DIRECTION	SEVERITY
DEPTH	ANGLE	DIRECTION	LENGTH	DEPTH	FEET	FEET	FEET	N/S	E/W	DEGS.	DG/100FT
FEET	DEGS.	DEGS.	FEET	FEET	FEET	FEET	FEET	FEET	FEET	FEET	FEET
7280.00	.50	N 28.00 W	93.00	7279.16	-33.62	67.75	20.21	E	70.70'	N 16.61 E	.58
7374.00	.30	N 19.00 W	94.00	7373.15	-34.23	68.35	19.95	E	71.20'	N 16.27 E	.22
7468.00	.20	N 85.00 E	94.00	7467.15	-34.30	68.65	20.14	E	71.54'	N 16.35 E	.42
7562.00	.30	S 87.00 E	94.00	7561.15	-34.02	68.66	20.55	E	71.66'	N 16.66 E	.11
7655.00	.10	N 42.00 W	93.00	7654.15	-34.10	68.88	20.66	E	71.92'	N 16.69 E	.41
7749.00	.40	N 53.00 E	94.00	7748.15	-34.33	69.25	20.69	E	72.27'	N 16.64 E	.45
7843.00	.60	N 66.00 E	94.00	7842.15	-34.13	69.66	21.40	E	72.88'	N 17.08 E	.24
7937.00	.20	N 03.00 E	94.00	7936.14	-34.24	70.18	21.75	E	73.47'	N 17.22 E	.57
8031.00	.40	N 08.00 E	94.00	8030.14	-34.55	70.67	21.80	E	73.95'	N 17.14 E	.21
8124.00	.10	S 78.00 E	93.00	8123.14	-34.49	70.87	22.10	E	74.24'	N 17.32 E	.45
8218.00	.80	N 72.00 E	94.00	8217.14	-34.00	70.91	22.83	E	74.50'	N 17.84 E	.76
8312.00	.30	N 13.00 E	94.00	8311.13	-34.04	71.55	23.41	E	75.28'	N 18.12 E	.74
8406.00	.10	N 21.00 W	94.00	8405.13	-34.28	71.87	23.39	E	75.58'	N 18.02 E	.24
8499.00	.20	S 64.00 W	93.00	8498.13	-34.48	71.95	23.18	E	75.59'	N 17.86 E	.25
8593.00	.80	S 04.00 E	94.00	8592.13	-34.28	71.28	22.80	E	74.84'	N 17.74 E	.80
8687.00	.70	S 29.00 E	94.00	8686.12	-33.21	70.11	23.14	E	73.83'	N 18.27 E	.36
8781.00	.20	S 85.00 W	94.00	8780.12	-33.03	69.56	22.85	E	73.22'	N 18.19 E	.85
8874.00	0.00	* * * * *	93.00	8873.12	-33.13	69.55	22.69	E	73.16'	N 18.07 E	.22
8968.00	1.00	S 48.00 W	94.00	8967.11	-33.18	69.00	22.08	E	72.45'	N 17.75 E	1.06
9062.00	1.10	S 63.00 W	94.00	9061.10	-33.49	68.03	20.67	E	71.10'	N 16.90 E	.31
9156.00	.50	S 46.00 W	94.00	9155.09	-33.70	67.27	19.60	E	70.06'	N 16.25 E	.68
9250.00	1.20	S 67.00 W	94.00	9249.08	-33.98	66.50	18.44	E	69.01'	N 15.50 E	.80
9343.00	1.10	S 55.00 W	93.00	9342.06	-34.49	65.60	16.82	E	67.72'	N 14.38 E	.28
9437.00	1.30	S 41.00 W	94.00	9436.04	-34.60	64.28	15.36	E	66.09'	N 13.43 E	.38
9531.00	1.30	S 36.00 W	94.00	9530.01	-34.36	62.62	14.03	E	64.17'	N 12.63 E	.12