STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

DISTRIBUTION	
BANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

CONDITIONS OF APPROVAL, IF ANYI

The Carlot take a second of the control of the carlot of t

UIL CONSERVATION DIVISION P. O. BOX 2088

Form C-103 Revised 10-1-78

SANTA FE, NEW MEXICO 87501	•
V.S.G.S.	5a, Indicate Type of Lease
LAND OFFICE	State X Fee
OPERATOR	5. State Oil & Gas Lease No. LG 3562
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FURM FOR PEROPOSALS TO DRILL ON TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	
	7. Unit Agreement Name
2. Name of Operator	8. Farm or Lease Name
rates retroteum corporation	Vacuum North ADJ St. Com
207 South 4th St., Artesia, NM 88210	9. Well No.
.,	10. Field and Pool, or Wildcat Undesignated
UNIT LETTER D . 833 PEET FROM THE NORTH LINE AND 660 PEET FROM	MMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMM
THE West LINE, SECTION 34 TOWNSHIP 16S RANGE 34E NMPM.	
	12. County
4008.5' GR	Lea
Check Appropriate Box To Indicate Nature of Notice, Report or Othe NOTICE OF INTENTION TO: SUBSEQUENT	
PERFORM REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON PLUG AND ABANDON REMEDIAL WORK TEMPORARILY ABANDON COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JOB	
OTHER Perforate, Treat	X
отнея	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including e work) SEE RULE 1903.	stimated date of starting any proposed
TD 13200 '.Perforated $10713-22$ ' and $10753-56$ ' (corrected perfs - previous $10745-48$ ') w/14 .50" holes. Acidized zone w/2500 gals 15% NEFE acid + 2% sealers.	sly reported as % KCL and 8 ball
Perforated 10185-195' w/11 .50" holes. Acidized perfs 10185-95' w/1500 g w/2% KCL and 22 ball sealers.	gals 15% NEFE acid
Acidized Wolfcamp perfs $10185-195$ ' w/4500 gals pad, 10000 gals 20% retard to 10917 ' and tested. Pulled packer to 10647 '. Acidized perfs $10713-7565000$ gals pad, 10000 gals 20% retarded acid and 12 ball sealers and 3500 20% retarded acid. Flushed w/250 bbls 1% KCL water.	5' in 2 stages:
TOOH w/packer.	
	,
18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
Production Supervisor	3-13-86
ORIGINAL SIGNED BY JERRY SEXTON	MAR 1 7 1986
APPROVED BY DISTRICT I SUPERVISOR TITLE	DATE HIMIN L