

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator David Fasken		8. Farm or Lease Name Berry Hobbs
3. Address of Operator 303 West Wall Ave., Suite 1901, Midland, TX 79701		9. Well No. 1
4. Location of Well UNIT LETTER M 990 FEET FROM THE South LINE AND 990 FEET FROM THE West LINE, SECTION 17 TOWNSHIP 16-S RANGE 36-E NMPM.		10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3937.2' GL		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-09-86: Spudded at 8:45 a.m., drilled 17½" hole to 398'.

5-10-86: Set 13-3/8", H-40, 48# casing at 399'. Cemented w/400 sx Class "C" + 2% CaCl. Cement circulated.

5-11-86 to 5-16-86: Drilling 12½" hole to 4296 feet.

5-17-86: Set 8-5/8", K-55, 24 & 32# casing @ 4300', cemented with 1825 sx Halliburton light w/¼# flocele & 15# salt/sk (12.9 ppg & 2.04 cuft/sk) plus 200 sx Class "C" w/2% CaCl (14.8 ppg & 1.32 cuft/sk). PD @ 8 a.m. 5-17-86. Circ. 10 sx excess cement.

5-18-86: WOC, set 8-5/8" slips, cut off 8-5/8" casing, NU BOP's.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED James F. Groce TITLE Agent DATE 5-19-86

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

DATE MAY 21 1986

RECEIVED
MAY 20 1986
O.C.D.
HOBBS OFFICE