

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. This form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	2125'	T. Canyon	10,747'	T. Ojo Alamo		T. Penn. "B"	
T. Salt	2193'	T. Strawn	(Lower) 11,210'	T. Kirtland-Fruitland		T. Penn. "C"	
D. Salt	2232'	T. Atoka	11,533' (smp)	T. Pictured Cliffs		T. Penn. "D"	
T. Yates	3182'	T. Miss		T. Cliff House		T. Leadville	
T. 7 Rivers		T. Devonian		T. Menefee		T. Madison	
T. Queen	4170'	T. Silurian		T. Point Lookout		T. Elbert	
T. Grayburg		T. Montoya		T. Mancos		T. McCracken	
T. San Andres	4907'	T. Simpson		T. Gallup		T. Ignacio Qtzite	
T. Glorieta	6277'	T. McKee		T. Base Greenhorn		T. Granite	
T. Paddock	6359'	T. Ellenburger		T. Dakota		T.	
T. Blinberry		T. Gr. Wash		T. Morrison		T.	
T. Tubb	7704'	T. Granite		T. Todilto		T.	
T. Drinkard	7822'	T. Delaware Sand		T. Entrada		T.	
T. Abo	8406'	T. Bone Springs		T. Wingate		T.	
T. Wolfcamp	9802'	T.		T. Chinle		T.	
T. Penn.	9965'	T.		T. Permian		T.	
T. Cisco (Bough C)	10,462'	T.		T. Penn. "A"		T.	

OIL OR GAS SANDS OR ZONES

No. 1, from	to	No. 4, from	to
No. 2, from	to	No. 5, from	to
No. 3, from	to	No. 6, from	to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from	to	feet
No. 2, from	to	feet
No. 3, from	to	feet
No. 4, from	to	feet

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
Surf.	230'	230'	Unconsolidated Sd & gravel	10,810	11,160	350'	Shale
230'	2125'	1895'	Red beds	11,160	11,180	20'	Lime
2125'	2190'	65'	Anhydrite	11,180	11,210	30'	Shale
2190'	3180'	990'	Salt	11,210	11,430	220'	Lime
3180'	4490'	1310'	Alt. Anhydrite, sand, shale gypsum	11,430	11,533'	103'	Sandy lime
				11,533'	11,547'	14'	Shale
4490'	4905'	415'	Anhydrite, sand, shale				
4905'	6950'	2045'	Dolomite w/sandstone & sh				
6950'	6995'	45'	Sandstone				
6995'	9800'	2805'	Dolomite w/Shale stingers				
9800'	10,000'	200'	Lime & shale				
10,000'	10,460'	460'	Shaly Lime				
10,460'	10,515'	55'	Lime				
10,515'	10,745'	230'	Lime & shale				
10,745'	10,810'	65'	Lime				