

# INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

## INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

### Southeastern New Mexico

T. Anhy 1,818'  
T. Salt \_\_\_\_\_  
B. Salt \_\_\_\_\_  
T. Yates 2,968'  
T. 7 Rivers \_\_\_\_\_  
T. Queen 3,802'  
T. Grayburg \_\_\_\_\_  
T. San Andres 4,545'  
T. Glorieta 6,124'  
T. Paddock \_\_\_\_\_  
T. Blinbry \_\_\_\_\_  
T. Tubb 7,364'  
T. Drinkard \_\_\_\_\_  
T. Abo \_\_\_\_\_  
T. Wolfcamp 9,796'  
T. Penn. \_\_\_\_\_  
T. Cisco (Bough C) 10,515'

T. Canyon 11,055'  
T. Strawn 11,547'  
T. Atoka \_\_\_\_\_  
T. Miss \_\_\_\_\_  
T. Devonian \_\_\_\_\_  
T. Silurian \_\_\_\_\_  
T. Montoya \_\_\_\_\_  
T. Simpson \_\_\_\_\_  
T. McKee \_\_\_\_\_  
T. Ellenburger \_\_\_\_\_  
T. Gr. Wash \_\_\_\_\_  
T. Granite \_\_\_\_\_  
T. Delaware Sand \_\_\_\_\_  
T. Bone Springs \_\_\_\_\_  
T. \_\_\_\_\_  
T. \_\_\_\_\_

### Northwestern New Mexico

T. Ojo Alamo \_\_\_\_\_  
T. Kirtland-Fruitland \_\_\_\_\_  
T. Pictured Cliffs \_\_\_\_\_  
T. Cliff House \_\_\_\_\_  
T. Menefee \_\_\_\_\_  
T. Point Lookout \_\_\_\_\_  
T. Mancos \_\_\_\_\_  
T. Gallup \_\_\_\_\_  
Base Greenhorn \_\_\_\_\_  
T. Dakota \_\_\_\_\_  
T. Morrison \_\_\_\_\_  
T. Todilto \_\_\_\_\_  
T. Entrada \_\_\_\_\_  
T. Wingate \_\_\_\_\_  
T. Chinle \_\_\_\_\_  
T. Permian \_\_\_\_\_  
T. Penn. "A" \_\_\_\_\_

T. Penn. "B" \_\_\_\_\_  
T. Penn. "C" \_\_\_\_\_  
T. Penn. "D" \_\_\_\_\_  
T. Leadville \_\_\_\_\_  
T. Madison \_\_\_\_\_  
T. Elbert \_\_\_\_\_  
T. McCracken \_\_\_\_\_  
T. Ignacio Qtzte \_\_\_\_\_  
T. Granite \_\_\_\_\_  
T. \_\_\_\_\_  
T. \_\_\_\_\_  
T. \_\_\_\_\_  
T. \_\_\_\_\_  
T. \_\_\_\_\_  
T. \_\_\_\_\_  
T. \_\_\_\_\_  
T. \_\_\_\_\_

### OIL OR GAS SANDS OR ZONES

No. 1, from 11,547' to TD 11,867' No. 4, from \_\_\_\_\_ to \_\_\_\_\_  
No. 2, from \_\_\_\_\_ to \_\_\_\_\_ No. 5, from \_\_\_\_\_ to \_\_\_\_\_  
No. 3, from \_\_\_\_\_ to \_\_\_\_\_ No. 6, from \_\_\_\_\_ to \_\_\_\_\_

### IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from \_\_\_\_\_ to \_\_\_\_\_ feet  
No. 2, from \_\_\_\_\_ to \_\_\_\_\_ feet  
No. 3, from \_\_\_\_\_ to \_\_\_\_\_ feet  
No. 4, from \_\_\_\_\_ to \_\_\_\_\_ feet

### FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1818	1818	Sand, Shale, Lime				
1,818	2968	1150	Salt, Anhydrite				
2,968	3802	834	Sand, Shale, Dolomite				
3,802	4545	743	Sand, Shale, Dolomite				
4,545	6124	1579	Dolomite, Shale				
6,124	7364	1240	Shale, Dolomite				
7,364	9796	2432	Dolomite, Shale, Sand				
9,796	10515	719	Lime, Shale				
10,515	11055	540	Lime, Shale				
11,055	11547	492	Lime, Shale				
11,547	11788	241	Lime, Sand, Shale TD				

RECEIVED  
MAY 19 1986  
C. C. P.  
HOBBS OFFICE