

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG WELLS TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	5a. Indicate Type of Lease State ☐ Fee ☒
2. Name of Operator Mitchell Energy Corporation	5. State Oil & Gas Lease No.
3. Address of Operator P.O. Box 4000, The Woodlands, TX 77387	7. Unit Agreement Name NA
4. Location of Well UNIT LETTER F 1900 FEET FROM THE North LINE AND 1650 FEET FROM THE West LINE, SECTION 32 TOWNSHIP 15-S RANGE 35-E N.M.P.M.	8. Farm or Lease Name Baer
	9. Well No. 1
	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether CF, RT, GR, etc.) 4003' GL	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☒	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 3-30-86 Moranco Rig #7 spudded 17-1/2" hole @ 700 hrs (MST). Drld to 373' and cmt'd 9 jts (374') 13-3/8" 54.5# K-55 8RD ST&C csg @ 373' by Halliburton w/425 sx (561 CF) Class "C" + 2% CaCl₂. Est mixing temp - 75° F, est BHT - 65° F. PD @ 1430 hrs (MST) w/600 psi. Circ 40 bbls cmt to pit. Tested BOP's to 1000 psi.
- 3-31-86 DNF @ 0300 hrs (MST). Total WOC time - 14-1/2 hrs, est comp strength 1200 psi.
- 4/1-4/86 Drld 12-1/4" hole to 3808'. Cmt'd 96 jts (3806') 8-5/8" 32# K-55 8RD ST&C csg @ 3806' by Halliburton w/1050 sx (2016 CF) Halliburton "Light" + 15% salt + 1/4 #/sk FC ar 400 sx (528 CF) Class "C" + 2% CaCl₂. Est mixing temp - 75° F, est BHT - 95° F. PD @ 1125 hrs (MST) 4-4-86 w/1400 psi. Circ 15 bbls cmt to pit. NU BOP's and tst'd rams to 5000 psi and hydril to 1500 psi.
- 4-05-86 DNF @ 1130 hrs (MST). Total WOC time - 24 hrs, est comp strength 1500 psi.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED G. W. Tullos G. W. Tullos TITLE District Drilling Manager DATE 4-7-86

Original signed by

APPROVED BY Paul Kautz

CONDITIONS OF APPROVAL, IF ANY:

TITLE OIL & GAS INSPECTOR

DATE APR 15 1986