

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-79

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
V-1026

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- P&A	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation	8. Farm or Lease Name Silverball ADT State
3. Address of Operator 105 South 4th St., Artesia, NM 88210	9. Well No. #1
4. Location of Well UNIT LETTER N 990 FEET FROM THE South LINE AND 2310 FEET FROM THE West LINE, SECTION 30 TOWNSHIP 14S RANGE 37E NMPM.	10. Field and Pool, or WHdcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3877.1' GR	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 11700'. Propose to plug and abandon well as follows:

Spot cement plug from 11700-11600' across TD.
Spot cement plug from 10025-9925' across Wolfcamp top @ 9975'.
Spot cement plug from 8376-8276' across Abo top @ 8326'.
Spot cement plug from 5900-5800' across Glorieta top @ 5850'.
Spot cement plug from 4875-4775' across 8 5/8" casing shoe @ 4825'.
Spot cement plug from 2345-2245' across Salado top @ 2295'.
Spot cement plug from 520-420' across 13 3/8" casing shoe @ 470'.
Set 15 sack plug at surface.

Verbal approval of foregoing given by Mr. Eddie Seay, N.M.O.C.D.-Hobbs, NM, on 5-16-86.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Albert L. Hall TITLE Engineer DATE 5-19-86

ORIGINAL SIGNED BY JERRY SEXTON
APPROVED BY DISTRICT SUPERVISOR TITLE _____ DATE MAY 20 1986

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
MAY 26 1986
C. C. D.
HOBBS OFFICE