

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-79

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
LG 8961	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation		8. Farm or Lease Name Sweet Thing AEB State
3. Address of Operator 105 South 4th St., Artesia, NM 88210		9. Well No. 1
4. Location of Well UNIT LETTER <u>J</u> , <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>1</u> TOWNSHIP <u>17S</u> RANGE <u>33E</u> NMPM.		10. Field and Pool, or Wildcat Undesignated Queen
15. Elevation (Show whether DF, RT, GR, etc.) 4143.5' GR		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

Spudded 26" hole at 3:00 PM 5-22-86 with Abbott Brothers rathole. Set 40' of 20" conductor. Notified June Goble with NMOCD, Hobbs, NM.
Resumed drilling 12-1/4" hole with rotary tools 3:30 PM 5-23-86.
Ran 9 joints 8-5/8" 24# J-55 casing, set at 406'. 1-Texas Pattern notched guide shoe set 406'. Regular insert float set 363'. Cemented w/275 sx Class "C" w/2% CaCl2. Compressive strength of cement - 1250 psi in 12 hrs. PD 10:30 PM 5-23-96. Bumped plug to 750 psi, released pressure and float held okay. Cement circulated 10 sx to pit. WOC. Drilled out 6:30 PM 5-24-86. WOC 19 hrs. Cut off and welded on flow nipple. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Jerry Sexton</u>	TITLE <u>Production Supervisor</u>	DATE <u>5-28-86</u>
ORIGINAL SIGNED BY JERRY SEXTON		
APPROVED BY <u>DISTRICT 1 SUPERVISOR</u>	TITLE _____	DATE <u>JUN 2 1986</u>
CONDITIONS OF APPROVAL, IF ANY:		

RECEIVED
MAY 29 1986
C. F. B.
HOUSE OFFICE