STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

·····	
DISTRIBUTION	
SANTA PE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

CONDITIONS OF APPROVAL, IF ANY:

Form C-103

 OIL CONSERVATION DIVISION						
P. O. BOX 2088						
SANTA FE, NEW MEXICO 87501						

DISTRIBU			ANTA EE NEW	MEXICO 97501		Revised 10-1-/8		
SANTA PE		SANTA FE, NEW MEXICO 87501			En Indicate Tun	Sa. Indicate Type of Lease		
U.S.O.S.					State XX	Fee [
LAND OFFIC	E	1				<u> </u>		
OPERATOR				•	5, State Oil & G	. ,		
					LG-4717			
	CLINIOD.	V NOTICES	AND REPORTS ON	WELLS				
(DO NOT US	SUNUR THIS FORM FOR PRO	POSALS TO DRILL	OR TO DEEPEN OR PLUG B	ACK TO A DIFFERENT RESERVOIR				
	USE "APPLICATI	ON FOR PERMIT -	(FBRIX C-101) FOR SUCI	PROPUSACS.	7. Unit Agreeme	nt Name		
۱. هند ا	GAS [T]				1			
WELL XX	werk L	OTHER-			8, Farm or Leas	e Name		
2. Name of Operator	•							
Hondo	Drilling Com	npany			Chevron	. State		
3, Address of Opera					9. Well No.			
P. O.	Drawer 2516.	. Midland.	Texas 79702-25	16	1			
4. Location of Well		,,			10. Field and P	ool, or Wildcat		
· • —			N 4- l-	660	North Sa	nmal-Penn		
UNIT LETTER	<u> </u>	L, 980 FEET	FROM THE NOTEN	LINE AND 660	PEET PROM	mmmm.		
THE Wes	t LINE, SECTIO	on8	township 15-S	RANGE	имем.	///////////////////////////////////////		
					7777777	<i>171111111</i>		
MITTI		//// 15. E	Levation (Show whether		12. County			
		(1111)	GR 4,259	.4'	Lea			
777777777	77777777		D T. I. I N	atura of Nation Page	er or Other Data			
				ature of Notice, Repo				
	NOTICE OF IN	ITENTION T	0:	SUBS	EQUENT REPORT OF	•		
								
PERFORM REMEDIAL	. WORK		PLUG AND ABANDON	REMEDIAL WORK	ALT:	ERING CASING		
TEMPORARILY ABAHI	DON			COMMENCE DRILLING OPHS.	PLUG	AND ABANDONMENT		
PULL OR ALTER CAS	7=4		CHANGE PLANS	CASING TEST AND CEMENT JOI				
PULL OR ALTER CAS	'''• <u></u>				and 13 3/8" casing	\mathbf{X}		
				<u> </u>				
OTHER								
17 Describe Propo	ned or Completed Or	perations (Clear)	y state all pertinent det	ails, and give pertinent dates,	, including estimated date o	starting any proposed		
work) SEE RUI		,	•	•	•			
10-3-86	Spudded 1.7	1/2" hole	at 2:00 p.m.					
10-4-86	Drilled to	450', ran	13 3/8" casing,	, set at 450'; ceme	ented with 400 sa	cks Class "H"		
	- 2% Ca.Cl.	. circulat	ed approximatel	Ly 75 sacks, plug o	lown at 12:15 a.m	. 10-5-86.		
10-11-86	Drilled 11	hole tot	al depth 4.450	, ran 108 Joints 3	32 lb. 8 5/8" cas	ing, total		
10-11-00	DITTIEC	noic, tot	tom Comented	with 1,500 sacks I	Howco It., 200 sa	cks Class "C"		
	or 4,439,	set on bot	. Louis Gemented	approximately 50 sa	acks coment Plu	g down 9:30		
	cement with	2% Ca. C1	., circulated a	on the process for	~ 30 minutes W	O.C. 24 hours.		
	p.m. Teste	.d. 8 5/8'' c	asing with 1,20	00 lb. pressure for	[Jo mindees. w.	o.o. 27 modro.		
10-13-86	Drilling 7	7/8" hole	to 4,933', Lime	e, bit #5.	•			
	_		•					
						•		
18. I hereby certify	that the information	above is true a	nd complete to the best	of my knowledge and belief.				
<າ ລ.	-							
	(1) (1)	•		President	Oct	ober 17, 1986		
SICHED CAN	XXXIIX		TITLE .	treardenr	DATE OCC			
_ · 		CARDO PO PACA						
Jaigin.	tal signed by "	ent (Bu a B air Solas Ba			A Commence of the Commence of	11 2 o 1900 -		
	DISTRICT I SUPER	(平)50署			DATE	y a say to the to		

HORE CALLER