

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

CO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

API No. 30-025-29816

3a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
3. State Oil & Gas Lease No.	
B-2229	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	
Name of Operator Phillips Petroleum Company	
Address of Operator 4001 Penbrook Street, Odessa, Texas 79762	
Location of Well UNIT LETTER <u>K</u> <u>1880</u> FEET FROM THE <u>south</u> LINE AND <u>1880</u> FEET FROM THE <u>west</u> LINE, SECTION <u>14</u> TOWNSHIP <u>17-S</u> RANGE <u>33-E</u> NMPM.	

7. Unit Agreement Name
8. Farm or Lease Name Phillips E State
9. Well No. 35
10. Field and Pool, or Wildcat Maljamar Grayburg-SA
12. County Lea

15. Elevation (Show whether DF, RT, GR, etc.)
4135.8' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUS AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUS AND ABANDONMENT <input type="checkbox"/>
FULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

1-04-87: Spud 12-1/4" hole at 7:30 P.M.

1-05-87: TD'd 12-1/4" hole at 10:15 P.M. Set 8-5/8" 24# K-55 ST&C casing at 1540' with 1000 sx Class "C" cement with 2% CaCl₂. Circ 200 sx. Displaced with 95 BFW.

1-06 & 07-87: Plugged down at 7:30 A.M. 1-06-87. WOC 18.25 hrs.

1-08 thru

1-11-87: Drlg. TD'd 7-7/8" holes at 11:00 A.M. 1-11-87: Schlumberger ran DLL-MSFL-GR-Cal, CNL-LDT-GR-Cal, CNL-GR-Cal, Log Space Sonic. TD at 4800'.

1-12-87: Set 5-1/2" 17# K-55 ST&C casing at 4800'. Cemented with 800 sx Class "C", 10% Diacel D, 9#/sx salt and 400 sx Class "C", 5#/sx salt. Displaced with 12 bbls 10% acetic acid, 98 bbls 2% KCL FW. Plugdown at 3:15 P.M. Circ 250 sx cmt. ND & set slips. WOCU.

I, I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Ralph J. Roper for W. J. Mueller

TITLE Engineering Supervisor, Reserv. DATE 1-15-87

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY

TITLE

DATE

JAN 19 1987

RECEIVED
JAN 16 1987
OCS
HONOLULU OFFICE