

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
LG-6638	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Hondo Drilling Company		8. Farm or Lease Name Barr "H" State
3. Address of Operator P. O. Drawer 2516, Midland, Texas 79702-2516		9. Well No. #1
4. Location of Well UNIT LETTER <u>I</u> <u>1,930</u> FEET FROM THE <u>South</u> LINE AND <u>890'</u> FEET FROM THE <u>East</u> LINE, SECTION <u>7</u> TOWNSHIP <u>16-S</u> RANGE <u>33-E</u> N.M.P.M.		10. Field and Pool, or Wildcat North Sanmal-Penn
15. Elevation (Show whether DF, RT, GR, etc.) GR 4,262.5'		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <u>13 3/8" and 8 5/8" casing</u> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

- 1-5-87 Spudded 17 1/2" hole at 10:30 p.m.
- 1-6-87 Drilled 17 1/2" hole to 451', ran 13 3/8" casing, total of 456', set at 450'; cemented with 400 sacks Class "H" cement, with 2% Ca. Cl. Cement circulated. Plugged down at 10:00 p.m.
- 1-13-87 Drilled 11" hole, total depth 4,425', ran 105 joints 32# 8 5/8" casing, total 4,445', set on bottom. Cemented with 1,500 sacks HOWCO Lt., 200 sacks Class "C" cement with 2% Ca. Cl. Cement circulated. Plugged down 12:30 p.m.
- 1-15-87 Drilling 7 7/8 " hole at 4,755', lime, bit #4.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry Sexton TITLE President DATE January 19, 1987

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT 1 SUPERVISOR

APPROVED BY _____ TITLE _____ DATE JAN 21 1987

CONDITIONS OF APPROVAL, IF ANY: