

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radioactivity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quadruplicate except on stone land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico				Northwestern New Mexico			
Rustler		Cisco		Ojo Alamo		Penn. "B"	
T. Anhy	2092	T. Canyon /Shale	11104	T. Kirtland-Fruitland		T. Penn. "C"	
T. Salt		T. Strawn	11402	T. Pictured Cliffs		T. Penn. "D"	
D. Salt		T. Atoka	11974	T. Cliff House		T. Leadville	
T. Yates	3276	T. Miss		T. Menefee		T. Madison	
T. 7 Rivers		T. Devonian		T. Point Lookout		T. Elbert	
T. Queen		T. Silurian		T. Mancos		T. McCracken	
T. Grayburg		T. Montoya		T. Gallup		T. Ignacio Qtzite	
T. San Andres	4939	T. Simpson		Base Greenhorn		T. Granite	
T. Glorieta		T. McKee		T. Dakota			
T. Paddock		T. Ellenburger		T. Morrison			
T. Elinebry		T. Gr. Wash		T. Todilto			
T. Tubb	7966	T. Granite		T. Entrada			
T. Drinkard	8085	T. Delaware Sand		T. Wingate			
T. Abo	8608	T. Bone Springs		T. Chinle			
T. Wolfcamp	10078	T.		T. Permian			
T. Penn.		T.		T. Penn. "A"			
T. Cisco (Bought C)	11018	T.					

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.	
No. 2, from.....to.....feet.	
No. 3, from.....to.....feet.	
No. 4, from.....to.....feet.	

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	470	470	Surface Shales, Redbeds				
470	2467	1997	Anhy				
2467	4300	1833	Anhy, Salt				
4300	5026	726	Dolo, Sd, Sh				
5026	6260	1234	Dolo				
6260	6520	260	Dolo, Cht, Anhy, Sh				
6520	7300	780	Dolo, Anhy				
7300	9638	2338	Dolo				
9638	9810	172	Dolo, Sh, Cht				
9810	10408	598	Dolo, cht				
10408	10690	282	Dolo, Sh, cht				
10690	11040	350	Dolo				
11040	11470	430	Dolo, Lm, Sh, cht				
11470	11870	400	Lm, Sh				
11870	12196	326	Lm, Sh, Sd				