

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. UNIT AGREEMENT NAME MCA	
2. NAME OF OPERATOR CONOCO INC.		8. FARM OR LEASE NAME MCA Unit	
3. ADDRESS OF OPERATOR P.O. Box 460, Hobbs, NM 88240		9. WELL NO. 369	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Unit E 1395' JNL & 1295' FWL		10. FIELD AND POOL, OR WILDCAT MALAMAR G/SA	
14. PERMIT NO. 30-025-29853		15. ELEVATIONS (Show whether OF, RT, GR, etc.) 3937' GL	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 29-175-32E		12. COUNTY OR PARISH LEA	
13. STATE NM			

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☒ Set production string

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work).*

Ran 96 gts 7 5/8", shoe at 4166'. Cement 1st stage w/lead slurry of 139 s4, class C light cmt w/18% Dact, 313 s4's class C. Drill slurry of 243 s4's, had 243 s4's cmt returns, bumped plug at 10:15 A.M. w/1200#. Float held. Open LV tool @ 2116'. Cement 2nd stage w/lead slurry of 724 s4's class C light w/18% Dact. Drill slurry of 100 s4's class C. Had 243 s4's cmt returns, bumped plug @ 3:50 p.m. w/2000#, float held. W.O.C. Shutoff wellhead.

18. I hereby certify that the foregoing is true and correct

SIGNED D.E. Finney
(This space for Federal or State office use)

TITLE Administrative Supervisor DATE March 25, 1987

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

ACCEPTED FOR RECORD

DATE MAR 30 1987

*See Instructions on Reverse Side

CARLSBAD, NEW MEXICO