

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRI
(Other instruction
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME mca
2. NAME OF OPERATOR CONOCO INC.	8. FARM OR LEASE NAME mca Unit
3. ADDRESS OF OPERATOR P.O. Box 460, Hobbs, N.M. 88240	9. WELL NO. 367
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface Unit 0 75' JSL & 1495' JEL	10. FIELD AND POOL, OR WILDCAT Majamaw G/SA
14. PERMIT NO. 30-025-29855	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 23-17S-32 E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4005' GL	12. COUNTY OR PARISH La
	13. STATE NM

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Set production string

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Run 5-1/2" 17# K-55, FL 54 (2312') ECP & DU collar & 5-1/2" 17# K-55, FL 45 (421'), 5-1/2" 17# K-55 8rd (1566'). Shoe at 4353. First stage cmt, lead slurry 365 sf class C light weight III w/2% S-1 (CaCl2) mixed 12.7 ppg, tail slurry 90 sf. Co2 treat cmt w/no cmt returns. Second stage cmt 300 sf class C w/2% S-1 (CaCl2) mixed 14.8 ppg w/25 sf returns to surface. Cut 5-1/2" CSG off & apply up.

ACCEPTED FOR RECORD

MAY 14 1987

CARLSBAD, NEW MEXICO

19. I hereby certify that the foregoing is true and correct

SIGNED

(This space for Federal or State office use)

TITLE Administrative Supervisor

DATE May 6, 1987

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side