

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)

Form approved.  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. UNIT AGREEMENT NAME MCA
2. NAME OF OPERATOR CONOCO INC.	8. FARM OR LEASE NAME MCA Unit 367
3. ADDRESS OF OPERATOR P.O. Box 460, Natchez, N.M. 88240	9. WELL NO. 367
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface Unit 0 75' SSL + 1495' SEL	10. FIELD AND POOL, OR WILDCAT Mojave G/SA
14. PERMIT NO. 30-025-29855	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 23-175-32 E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4005' GL	12. COUNTY OR PARISH La
	13. STATE NM

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
(Other) ☐

PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
ABANDON\* ☐  
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐  
FRACTURE TREATMENT ☐  
SHOOTING OR ACIDIZING ☐  
(Other) ☒ Set intermediate csg

REPAIRING WELL ☐  
ALTERING CASING ☐  
ABANDONMENT\* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Run 8-5/8" - 32#, J-55 8<sup>th</sup> int CSG, with shoe @ 2353'. Collar at 2310'. DV tool + ECP @ 1617' cmt'd first stage w/lead slurry of 670 sf class C light w/18% aact. Soil slurry of 120 sf class C w/2% CACL<sub>2</sub>, 132 sf to surface. Bmpd plug. Second stage lead slurry 400 sf class C w/2% CACL<sub>2</sub>, 110 sf to surface, bmpd plug, cut csg off, sent. csg set in 80,000 # tension.

ACCEPTED FOR RECORD

MAY 14 1987

CARLSBAD NEW MEXICO

I hereby certify that the foregoing is true and correct

SIGNED D.F. Finney  
(This space for Federal or State office use)

TITLE Administrative Supervisor DATE May 6, 1987

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

\*See Instructions on Reverse Side