

MINIMUM PREVENTER EQUIPMENT REQUIREMENTS
(ATTACHMENT NO. _____ TO BID SHEET AND WELL SPECIFICATIONS)

3000 PSI WORKING PRESSURE
TO BE INSTALLED AFTER SETTING 8 5/8 INCH CASING

No.	Item	Min. Size	Type	Press. Rating	Furnished By	
					Contr.	
1.	Flow Line	8"	Weld	125		
2.	Fill Up Line	2"	Thd or Weld	125		
3.	Bell Nipple	8"	Weld	125		
4.	Rotating Head					
5.	Hydraulically Operated Gate Valve					
6.	Bleed Line					
7.	Bag Preventer	8"	Flanged	3000		
8.	Hydraulically Operated Ram Preventer					
9.	Drilling Spool with <u>2</u> in. and <u>2</u> in. Side Outlets	8"	Flanged	3000		
10.	Preventers Side Outlets <u>2</u> in. and <u>2</u> in. Use as alternate to No. 9 above.	8"	Flanged	3000		
11.	Gate Valve	2"	Flanged	3000		
12.	Hydraulically Operated Gate Valve (HCR Valve)					
13.	Line to Choke Manifold	2"	Flanged	3000		
14.	Gate Valve	2"	Flanged	3000		
15.	Hydraulically Operated Gate Valve					
16.	Check Valve					
17.	Drilling Spool with _____ in. and _____ in. Side outlets					
18.	Preventer Side Outlets _____ in. and _____ in.					
19.	Gate Valve	2"	Flanged	3000		
20.	Hydraulically Operated Gate Valve					
21.	Relief Line					
22.	Wear Flange or Bushing					
23.	Kill Line to accessible location approx. _____ ft. from rig. (MINIMUM DISTANCE)					
24.	Gate Valve					
25.	Kill Line to rig pump manifold	2"	Flanged	3000		
26.	_____ Way Cross, _____ in. x _____ in. x _____ in. x _____ in.					
27.	Tee, _____ in. x _____ in. x _____ in.					
28.	Bull Plug					
29.	Casing Spool					
30.	Gate Valve					
31.	Casing Spool					
32.	Gate Valve					
33.	Pressure Gauge					
34.	Casing Head	8"	Flanged	3000		
35.	Gate Valve					
36.	Gate Valve					

Line sizes to be inside diameter.

Valves, spools and preventers sizes to be bore dimension.