

## HALLIBURTON SERVICES -

TICKET NUMBER: 54826401

TEST DATE: 10-29-87

CLOCK NUMBER: 5979

HOUR: 24

GAUGE NUMBER: 8040

GAUGE DEPTH: 10715.0



F00014 0001 66 12 00

| REFERENCE | TIME<br>(MINUTES) | PRESSURE<br>(PSI) | DP | (T+DT)<br>-----<br>(T+DT) | (T+DT)<br>LOG-----<br>DT |
|-----------|-------------------|-------------------|----|---------------------------|--------------------------|
|-----------|-------------------|-------------------|----|---------------------------|--------------------------|

## FIRST FLOW

|   |   |     |       |      |  |
|---|---|-----|-------|------|--|
| B | 1 | 0.0 | 320.7 |      |  |
| C | 2 | 1.7 | 343.3 | 22.6 |  |

## FIRST CLOSED-IN

|   |    |      |        |        |           |
|---|----|------|--------|--------|-----------|
| C | 1  | 0.0  | 343.3  |        |           |
|   | 2  | 9.0  | 3834.8 | 3491.5 | 1.4 0.073 |
|   | 3  | 10.0 | 3887.7 | 3544.5 | 1.4 0.067 |
|   | 4  | 12.0 | 3931.5 | 3588.2 | 1.5 0.056 |
|   | 5  | 14.0 | 3936.3 | 3593.0 | 1.5 0.049 |
|   | 6  | 16.0 | 3941.1 | 3597.8 | 1.5 0.043 |
|   | 7  | 18.0 | 3943.9 | 3600.7 | 1.5 0.038 |
|   | 8  | 20.0 | 3946.4 | 3603.1 | 1.5 0.035 |
|   | 9  | 22.0 | 3948.8 | 3605.5 | 1.5 0.032 |
|   | 10 | 24.0 | 3951.0 | 3607.7 | 1.5 0.029 |
|   | 11 | 26.0 | 3952.2 | 3608.9 | 1.6 0.027 |
|   | 12 | 28.0 | 3953.4 | 3610.1 | 1.6 0.025 |
|   | 13 | 30.0 | 3954.5 | 3611.3 | 1.6 0.023 |
|   | 14 | 35.0 | 3957.0 | 3613.7 | 1.6 0.020 |
|   | 15 | 40.0 | 3959.1 | 3615.8 | 1.6 0.018 |
|   | 16 | 45.0 | 3961.1 | 3617.9 | 1.6 0.016 |
|   | 17 | 50.0 | 3963.0 | 3619.7 | 1.6 0.014 |
|   | 18 | 55.0 | 3964.4 | 3621.2 | 1.6 0.013 |
|   | 19 | 60.0 | 3135.7 | 2792.5 | 1.6 0.012 |
| D | 20 | 60.4 | 3766.6 | 3623.3 | 1.6 0.012 |

## SECOND FLOW

|   |    |      |        |       |
|---|----|------|--------|-------|
| E | 1  | 0.0  | 454.7  |       |
|   | 2  | 7.0  | 784.3  | 329.6 |
|   | 3  | 14.0 | 1063.5 | 279.1 |
|   | 4  | 21.0 | 1294.4 | 231.0 |
|   | 5  | 28.0 | 1416.5 | 122.0 |
|   | 6  | 35.0 | 1595.4 | 179.0 |
|   | 7  | 42.0 | 1753.2 | 157.7 |
|   | 8  | 49.0 | 1905.2 | 152.1 |
|   | 9  | 56.0 | 2053.9 | 148.6 |
|   | 10 | 63.0 | 2186.8 | 133.0 |
|   | 11 | 70.0 | 2306.9 | 120.1 |
|   | 12 | 77.0 | 2417.5 | 110.6 |
|   | 13 | 84.0 | 2523.0 | 105.5 |

"NOTICE: THIS REPORT IS BASED ON SOUND ENGINEERING PRACTICES, BUT BECAUSE OF VARIABLE WELL CONDITIONS AND OTHER INFORMATION WHICH MUST BE RELIED UPON HALLIBURTON MAKES NO WARRANTY, EXPRESS OR IMPLIED AS TO THE ACCURACY OF THE DATA OR OF ANY CALCULATIONS OR OPINIONS EXPRESSED HEREIN. YOU AGREE THAT HALLIBURTON SHALL NOT BE LIABLE FOR ANY LOSS OR DAMAGE, WHETHER DUE TO NEGLIGENCE OR OTHERWISE, ARISING OUT OF OR IN CONNECTION WITH SUCH DATA, CALCULATIONS OR OPINIONS."

