

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-73

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation		8. Farm or Lease Name Burton AER Com
3. Address of Operator 105 South 4th St., Artesia, NM 88210		9. Well No. 1
4. Location of Well UNIT LETTER <u>J</u> <u>2400</u> FEET FROM THE <u>South</u> LINE AND <u>1850</u> FEET FROM THE <u>East</u> LINE, SECTION <u>26</u> TOWNSHIP <u>16S</u> RANGE <u>37E</u> NMPM.		10. Field and Pool, or Wildcat Casey Strawn
15. Elevation (Show whether DF, RT, GR, etc.) 3765.2' GR		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

Spudded 17-1/2" hole at 8:00 AM 10-5-87. Notified Eddie Seay, NMOCD, Hobbs, NM, of spud. Ran 16 joints 13-3/8" 54.5# J-55 casing set at 458'. 1-Texas Pattern notched guide shoe set 458', insert float set 427'. Cemented w/450 sx Class "C" with 2% CaCl<sub>2</sub> (yield 1.32, weight 14.8). PD 9:00 PM 10-5-87. Bumped plug to 600 psi, released pressure and float held okay. Cement circulated 50 sacks to pit. WOC.

Drilled out 11:30 AM 10-6-87. WOC 14 hrs and 30 minutes. NU and tested. Reduced hole to 11". Drilled plug and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Paul Kautz TITLE Production Supervisor DATE 10-7-87

Orig. Signed by  
Paul Kautz  
Geologist

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE OCT 15 1987

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED  
OCT 9 1987  
OCD  
HOBBS OFFICE